

屋内照明器具特性	
品番 (品名)	X F X 4 5 7 G E W
光源	LED4000_85_4880 ×1 4880.0 lm
管理番号	K0192146 (0) D 1
B Z 分類	B Z 4

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
			室指数	照明率 (X 0 . 0 1)																				Z C M	
保守率		良 中 否	0 . 8 1	0 . 6	5 9	4 8	4 0	3 5	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 4	4 5	3 9	3 5	3 3				
			0 . 7 7	0 . 8	7 0	5 9	5 2	4 7	6 8	5 8	5 1	4 6	6 6	5 7	5 1	4 6	6 4	5 6	5 0	4 6	4 4				
			0 . 6 8	1 . 0	7 7	6 7	6 0	5 5	7 5	6 6	6 0	5 4	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 4	5 2				
				1 . 2 5	8 3	7 4	6 8	6 2	8 1	7 3	6 7	6 2	7 8	7 1	6 6	6 2	7 6	7 0	6 5	6 1	5 9				
下方投影面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 5	7 0	6 7	6 4					
等価発光面積			c m ²	2 . 0	9 2	8 6	8 0	7 6	9 1	8 5	8 0	7 6	8 8	8 3	7 8	7 5	8 5	8 1	7 7	7 4	7 2				
取付高さ	器具間隔最大限			2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 7				
	横方向 (A)		縦方向 (B)	3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 6	8 4	9 1	8 8	8 5	8 3	8 0				
1 . 5m	1 . 9 m	2 . 1 2 m		4 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	8 5				
2	2 . 5 2	2 . 6 6		5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 3	9 1	9 5	9 4	9 2	9 0	8 7				
2 . 5	3 . 1 3	3 . 2 3		7 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 1				
3	3 . 7 4	3 . 8 1		1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3				

