

屋内照明器具特性	
品番 (品名)	X F X 4 2 0 Z E N
光源	LED5000_85_2290 ×1 2290.0 l m
管理番号	K0192167 (0) DR 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		9 7 %																				
保守率		良 中 否	0 . 7 7	0 . 6	5 6	4 4	3 6	3 0	5 4	4 3	3 5	3 0	5 2	4 2	3 5	3 0	4 9	4 0	3 4	2 9	2 7	
			0 . 7 2	0 . 8	6 6	5 4	4 6	4 0	6 4	5 3	4 6	4 0	6 1	5 1	4 5	4 0	5 8	5 0	4 4	3 9	3 7	
			0 . 6 8	1 . 0	7 2	6 1	5 3	4 7	7 0	6 0	5 3	4 7	6 7	5 8	5 2	4 7	6 4	5 6	5 1	4 6	4 3	
			1 . 2 5	7 8	6 8	6 1	5 5	7 6	6 7	6 0	5 4	7 3	6 5	5 9	5 4	6 9	6 3	5 7	5 3	5 0		
下方投影面積		c m ²	1 . 5	8 2	7 3	6 6	6 0	8 0	7 2	6 5	6 0	7 7	6 9	6 4	5 9	7 3	6 7	6 2	5 8	5 5		
			等価発光面積		c m ²	2 . 0	8 8	8 0	7 4	6 8	8 6	7 9	7 3	6 8	8 2	7 6	7 1	6 7	7 9	7 4	6 9	6 5
取付高さ	器具間隔最大限		2 . 5	9 1	8 5	7 9	7 4	8 9	8 3	7 8	7 3	8 6	8 0	7 6	7 2	8 2	7 8	7 4	7 1	6 7		
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 8	8 3	7 8	9 2	8 6	8 2	7 8	8 8	8 4	8 0	7 6	8 5	8 1	7 8	7 5	7 1		
1 . 5 m	1 . 9 6 m	2 . 1 5 m	4 . 0	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 3	9 2	8 8	8 5	8 1	8 8	8 5	8 2	8 0	7 6		
2	2 . 5 8	2 . 6 8	5 . 0	9 9	9 5	9 1	8 8	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 0	8 8	8 5	8 3	8 0		
2 . 5	3 . 2 1	3 . 2 4	7 . 0	1 0 1	9 8	9 5	9 3	9 9	9 7	9 4	9 2	9 6	9 4	9 2	8 9	9 3	9 1	8 9	8 7	8 4		
3	3 . 8 4	3 . 8 1	1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 7	9 5	9 8	9 6	9 5	9 3	9 5	9 3	9 2	9 1	8 7		

