

# 屋内照明器具特性

品番 (品名)	NNCF50120 (JYOUJI)															
光源	LED5000_85_900 x1 900.0 l m															
管理番号	K0170339 (1) DR 1															
BZ分類	BZ6/3.5/BZ7															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	49 %																			
下方光束	51 %																			
室指数	照明率 ( X0.01) ZCM																			
保守率	良 中 否	0.81	0.6	48	36	28	23	44	33	26	22	37	28	23	19	30	24	19	16	11
		0.77	0.8	56	45	37	31	52	41	34	29	43	35	30	25	35	29	25	22	15
		0.68	1.0	62	51	43	37	57	47	40	35	48	40	35	30	39	33	29	26	18
			1.25	67	57	49	44	62	53	46	41	52	45	40	35	43	37	33	30	21
下方投影面積		c m <sup>2</sup>																		
等価発光面積		c m <sup>2</sup>																		
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	0.00 H m	1.74 H m	2.5	80	73	67	61	74	67	62	57	62	57	53	49	51	48	44	42	29
			3.0	82	76	70	65	76	70	65	61	64	60	56	53	53	50	47	44	32
			4.0	85	80	75	71	79	74	70	66	67	63	60	57	56	53	51	48	35
			5.0	87	83	79	75	81	77	73	70	69	66	63	60	57	55	53	51	37
			7.0	90	86	83	80	84	80	77	75	71	69	67	64	60	58	56	54	39
			10.0	92	89	87	84	85	83	81	79	73	71	69	68	61	60	59	57	42

