

屋内照明器具特性	
品番 (品名)	XF X4 4 1 F HN
光源	LED5000_85_2700 ×1 2700.0 lm
管理番号	K0192931 (0) DB 1
B Z 分類	BZ2 / 2.8 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 8 1	0 . 6	6 7	5 7	5 1	4 7	6 6	5 7	5 1	4 7	6 4	5 6	5 1	4 7	6 2	5 5	5 0	4 6	4 5
			0 . 7 7	0 . 8	7 8	7 0	6 4	6 0	7 7	6 9	6 4	6 0	7 5	6 8	6 3	5 9	7 3	6 7	6 2	5 9	5 7
			1 . 0	8 5	7 7	7 2	6 8	8 4	7 7	7 2	6 8	8 1	7 5	7 1	6 7	7 9	7 4	7 0	6 7	6 5	
			0 . 6 8	1 . 2 5	9 0	8 3	7 9	7 5	8 9	8 3	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 7	7 4	7 2
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 3	8 7	8 3	7 9	9 2	8 7	8 2	7 9	9 0	8 5	8 1	7 9	8 7	8 4	8 1	7 8	7 6	
			2 . 0	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 2	
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 5	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7	
1 . 5 m	2 . 2 1 m	2 . 0 5 m	4 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 6	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 0	
2	2 . 9 3	2 . 5 9	5 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2	
2 . 5	3 . 6 6	3 . 1 4	7 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4	
3	4 . 3 8	3 . 7	1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6	

