

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X4 4 5 GHN                |
| 光源       | LED5000_85_3580 ×1 3580.0 lm |
| 管理番号     | K0192610 ( 0 ) DB 1          |
| B Z 分類   | BZ4 / 0.9 / BZ3              |

| 器具効率   |  | 100 %           | 反射率    | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |    |
|--------|--|-----------------|--------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|------|----|----|----|-----|----|----|
|        |  |                 |        | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |    |
|        |  |                 |        | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |    |
| 上方光束   |  | 4 %             | 室指数    | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |    |    |    |      |    |    |    |     | Z  | CM |
| 下方光束   |  | 96 %            |        |               |      |     |     |     |      |     |     |     |      |    |    |    |      |    |    |    |     |    |    |
| 保守率    |  | 良<br>中<br>否     | 0.81   | 0.6           | 60   | 49  | 42  | 37  | 59   | 48  | 41  | 36  | 56   | 47 | 41 | 36 | 54   | 46 | 40 | 36 | 34  |    |    |
|        |  |                 | 0.77   | 0.8           | 70   | 60  | 53  | 48  | 69   | 59  | 52  | 47  | 66   | 57 | 51 | 47 | 63   | 56 | 51 | 46 | 44  |    |    |
|        |  |                 | 0.68   | 1.0           | 77   | 67  | 61  | 56  | 75   | 66  | 60  | 55  | 72   | 65 | 59 | 55 | 69   | 63 | 58 | 54 | 51  |    |    |
|        |  |                 |        | 1.25          | 83   | 74  | 68  | 63  | 81   | 73  | 67  | 63  | 78   | 71 | 66 | 62 | 75   | 69 | 65 | 61 | 58  |    |    |
| 下方投影面積 |  | cm <sup>2</sup> |        | 1.5           | 87   | 79  | 73  | 68  | 85   | 78  | 72  | 68  | 81   | 75 | 71 | 67 | 78   | 73 | 69 | 66 | 63  |    |    |
|        |  |                 |        | 2.0           | 92   | 85  | 80  | 76  | 90   | 84  | 79  | 75  | 86   | 82 | 78 | 74 | 83   | 79 | 76 | 73 | 70  |    |    |
| 等価発光面積 |  | cm <sup>2</sup> |        | 2.5           | 95   | 89  | 85  | 81  | 93   | 88  | 84  | 80  | 90   | 85 | 82 | 79 | 86   | 83 | 80 | 77 | 74  |    |    |
|        |  |                 |        | 3.0           | 97   | 92  | 88  | 85  | 95   | 91  | 87  | 84  | 92   | 88 | 85 | 82 | 88   | 86 | 83 | 81 | 77  |    |    |
| 1.5m   |  | 1.83 m          | 2.16 m |               | 4.0  | 99  | 96  | 93  | 90   | 98  | 94  | 92  | 89   | 94 | 92 | 89 | 87   | 91 | 89 | 87 | 85  | 82 |    |
| 2      |  | 2.42            | 2.71   |               | 5.0  | 101 | 98  | 95  | 93   | 99  | 97  | 94  | 92   | 96 | 94 | 92 | 90   | 93 | 91 | 89 | 88  | 84 |    |
| 2.5    |  | 3.01            | 3.29   |               | 7.0  | 103 | 101 | 99  | 97   | 101 | 99  | 97  | 96   | 98 | 96 | 95 | 93   | 95 | 94 | 92 | 91  | 87 |    |
| 3      |  | 3.6             | 3.88   |               | 10.0 | 104 | 103 | 101 | 100  | 103 | 101 | 100 | 99   | 99 | 98 | 97 | 96   | 96 | 95 | 94 | 94  | 90 |    |

