

屋内照明器具特性	
品番 (品名)	XAD3401
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178952 (0) DR1
BZ分類	BZ4/2.8/BZ3

器具効率		74 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	44	35	30	26	43	35	30	26	41	34	29	26	40	33	29	26	25
			0.63	0.8	51	44	38	34	50	43	38	34	49	42	38	34	47	41	37	34	33
			0.56	1.0	56	49	44	40	55	49	44	40	53	48	43	40	52	47	43	40	38
				1.25	61	55	50	46	60	54	49	46	58	53	49	46	56	51	48	45	44
下方投影面積		cm ²	1.5	64	58	54	50	63	57	53	50	61	56	52	49	59	55	52	49	47	
			2.0	68	63	59	56	67	62	59	56	65	61	58	55	63	60	57	55	53	
取付高さ	器具間隔最大限		2.5	70	66	63	60	69	65	62	60	67	64	61	59	65	63	60	58	57	
	横方向 (A)	縦方向 (B)	3.0	72	68	65	63	71	68	65	62	69	66	64	62	67	65	63	61	59	
H m	1.24 H m	1.25 H m	4.0	74	71	69	67	73	70	68	66	71	69	67	65	69	67	66	64	62	
			5.0	75	73	71	69	74	72	70	68	72	70	69	67	70	69	68	66	64	
			7.0	76	75	73	72	75	74	72	71	73	72	71	70	72	71	70	69	67	
			10.0	77	76	75	74	76	75	74	73	75	74	73	72	73	72	71	71	69	

