

屋内照明器具特性	
品番 (品名)	S L B 8 1 3 0 1
光源	L L D 2 4 2 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 4 7 9 0 (0) D R 1
B Z 分類	B Z 1

器具効率		9 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 9 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		4 8 %																				
保守率		良	0 . 6 7	0 . 6	6 1	5 3	4 8	4 5	5 8	5 1	4 7	4 4	5 2	4 7	4 3	4 1	4 6	4 2	4 0	3 8	3 4	
		中	0 . 6 3	0 . 8	6 8	6 1	5 6	5 2	6 4	5 8	5 3	5 0	5 7	5 2	4 9	4 6	5 0	4 7	4 5	4 3	3 7	
		否	0 . 5 6	1 . 0	7 3	6 6	6 1	5 7	6 8	6 2	5 8	5 5	6 0	5 6	5 3	5 0	5 2	5 0	4 8	4 6	3 9	
				1 . 2 5	7 6	7 0	6 6	6 2	7 2	6 7	6 3	6 0	6 3	5 9	5 6	5 4	5 5	5 2	5 0	4 9	4 1	
下方投影面積		c m ²	1 . 5	7 9	7 4	6 9	6 6	7 4	7 0	6 6	6 3	6 5	6 2	5 9	5 7	5 6	5 4	5 2	5 1	4 2		
等価発光面積			c m ²	2 . 0	8 3	7 8	7 4	7 1	7 7	7 4	7 0	6 8	6 7	6 5	6 3	6 1	5 8	5 6	5 5	5 4	4 3	
取付 高さ	器具間隔最大限		2 . 5	8 5	8 1	7 8	7 5	7 9	7 6	7 3	7 1	6 9	6 7	6 5	6 3	5 9	5 8	5 7	5 6	4 4		
	横方向 (A) 縦方向 (B)		3 . 0	8 6	8 3	8 0	7 8	8 1	7 8	7 6	7 3	7 0	6 8	6 7	6 5	6 0	5 9	5 8	5 7	4 5		
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	8 8	8 6	8 3	8 1	8 2	8 0	7 8	7 7	7 1	7 0	6 9	6 7	6 1	6 0	5 9	5 9	4 6		
			5 . 0	8 9	8 7	8 5	8 4	8 4	8 2	8 0	7 9	7 2	7 1	7 0	6 9	6 2	6 1	6 0	6 0	4 6		
			7 . 0	9 1	8 9	8 8	8 6	8 5	8 3	8 2	8 1	7 3	7 2	7 2	7 1	6 3	6 2	6 1	6 1	4 7		
			1 0 . 0	9 2	9 1	9 0	8 9	8 6	8 5	8 4	8 3	7 4	7 3	7 3	7 2	6 3	6 3	6 2	6 2	4 7		

