

屋内照明器具特性	
品番 (品名)	S L B 8 1 3 0 7
光源	L L D 3 4 2 1 L C B 1 × 1 7 0 0 . 0 1 m
管理番号	K 0 1 9 5 4 2 8 (0) D R 1
B Z 分類	B Z 1

器具効率		9 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		4 8 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		4 8 %																					
保守率		良	0 . 6 7	0 . 6	6 1	5 3	4 8	4 5	5 8	5 1	4 7	4 4	5 1	4 7	4 3	4 1	4 6	4 2	4 0	3 8	3 4		
		中	0 . 6 3	0 . 8	6 8	6 1	5 6	5 2	6 4	5 8	5 3	5 0	5 6	5 2	4 9	4 6	5 0	4 7	4 4	4 3	3 7		
		否	0 . 5 6	1 . 0	7 2	6 6	6 1	5 7	6 8	6 2	5 8	5 5	6 0	5 6	5 3	5 0	5 2	5 0	4 8	4 6	3 9		
				1 . 2 5	7 6	7 0	6 6	6 2	7 1	6 6	6 2	5 9	6 3	5 9	5 6	5 4	5 4	5 2	5 0	4 9	4 1		
下方投影面積		c m ²		1 . 5	7 9	7 3	6 9	6 6	7 4	6 9	6 6	6 3	6 5	6 1	5 9	5 7	5 6	5 4	5 2	5 1	4 2		
等価発光面積		c m ²		2 . 0	8 2	7 8	7 4	7 1	7 7	7 3	7 0	6 8	6 7	6 5	6 2	6 1	5 8	5 6	5 5	5 4	4 3		
取付 高さ	器具間隔最大限			2 . 5	8 5	8 1	7 8	7 5	7 9	7 6	7 3	7 1	6 9	6 7	6 5	6 3	5 9	5 8	5 7	5 5	4 4		
	横方向 (A)		縦方向 (B)	3 . 0	8 6	8 3	8 0	7 7	8 0	7 8	7 5	7 3	7 0	6 8	6 6	6 5	6 0	5 9	5 8	5 7	4 5		
H m	0 . 4 0 H m		0 . 4 0 H m	4 . 0	8 8	8 5	8 3	8 1	8 2	8 0	7 8	7 6	7 1	7 0	6 8	6 7	6 1	6 0	5 9	5 8	4 6		
				5 . 0	8 9	8 7	8 5	8 3	8 3	8 1	8 0	7 8	7 2	7 1	7 0	6 9	6 2	6 1	6 0	6 0	4 6		
				7 . 0	9 0	8 9	8 7	8 6	8 5	8 3	8 2	8 1	7 3	7 2	7 1	7 1	6 2	6 2	6 1	6 1	4 7		
				1 0 . 0	9 1	9 0	8 9	8 8	8 5	8 5	8 4	8 3	7 4	7 3	7 3	7 2	6 3	6 3	6 2	6 2	4 7		

