

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 9 1 W Z
光源	LDA4 L - G - E17 / Z40E / S / W / 2 × 1 440.0 1 m
管理番号	K0130460 ( 0 ) DB 1
BZ分類	BZ8 / 4.5 / BZ7

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
上方光束	27 %	床	10 %				10 %				10 %				10 %				0 %
下方光束	30 %		10 %				10 %				10 %				10 %				0 %
室指数		照明率 ( X0.01 )																ZCM	
保守率	良 0.63	0.6	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	8	1.6	1.2	9	7	4
	中 0.6	0.8	3.0	2.3	1.9	1.5	2.8	2.2	1.7	1.4	2.3	1.8	1.5	1.2	1.9	1.5	1.2	1.0	6
	否 0.56	1.0	3.4	2.7	2.2	1.9	3.1	2.5	2.1	1.7	2.6	2.1	1.8	1.5	2.1	1.7	1.5	1.2	8
下方投影面積	cm <sup>2</sup>	1.25	3.7	3.1	2.6	2.2	3.4	2.8	2.4	2.1	2.8	2.4	2.1	1.8	2.3	2.0	1.7	1.5	1.0
		1.5	3.9	3.3	2.9	2.5	3.6	3.1	2.7	2.4	3.0	2.6	2.3	2.0	2.5	2.1	1.9	1.7	1.1
等価発光面積	cm <sup>2</sup>	2.0	4.2	3.7	3.3	3.0	3.9	3.5	3.1	2.8	3.3	2.9	2.6	2.4	2.7	2.4	2.2	2.0	1.4
		2.5	4.5	4.0	3.6	3.3	4.1	3.7	3.4	3.1	3.5	3.1	2.9	2.6	2.8	2.6	2.4	2.2	1.5
取付高さ	器具間隔最大限		3.0	4.6	4.2	3.9	3.6	4.3	3.9	3.6	3.3	3.6	3.3	3.1	2.9	3.0	2.7	2.6	1.7
	横方向 (A)	縦方向 (B)	4.0	4.8	4.5	4.2	3.9	4.4	4.2	3.9	3.7	3.8	3.5	3.3	3.1	3.1	2.9	2.8	1.9
Hm	1.30Hm	2.10Hm	5.0	4.9	4.6	4.4	4.2	4.6	4.3	4.1	3.9	3.9	3.7	3.5	3.3	3.2	3.1	2.9	2.0
			7.0	5.1	4.9	4.7	4.5	4.7	4.5	4.3	4.2	4.0	3.9	3.7	3.6	3.4	3.3	3.1	2.2
			10.0	5.2	5.0	4.9	4.7	4.8	4.7	4.5	4.4	4.1	4.0	3.9	3.8	3.5	3.4	3.3	2.4

