

屋内照明器具特性	
品番 (品名)	NNFS 4 2 0 0 1 J
光源	LDL40S.L / 22 / 21 (2100) ×2 2100.0 1 m
管理番号	K0125684 (2) DB 1
BZ分類	BZ6

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	15 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	83 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	50	38	30	24	48	36	29	24	44	34	27	23	40	32	26	22	19	
		0.8	59	47	39	33	57	46	38	32	52	43	36	31	48	40	34	29	26	
		1.0	66	54	46	39	63	52	44	39	58	49	42	37	53	46	40	35	31	
		1.25	71	61	52	46	68	59	51	45	63	55	48	43	58	51	46	41	37	
下方投影面積	c m ²	1.5	75	65	58	51	72	63	56	50	67	59	53	48	61	55	50	46	41	
		2.0	81	72	65	60	78	70	64	58	72	65	60	55	66	61	57	53	47	
取付高さ	器具間隔最大限		2.5	85	77	71	65	81	75	69	64	75	70	65	61	70	65	61	58	52
	横方向 (A)	縦方向 (B)	3.0	87	81	75	70	84	78	73	68	78	73	69	65	72	68	65	61	55
1.5m	2.2 m	2.19 m	4.0	91	85	80	76	88	83	78	74	82	77	74	70	76	72	69	67	60
2	2.91	2.76	5.0	93	88	84	80	90	85	82	78	84	80	77	74	78	75	73	70	64
2.5	3.61	3.35	7.0	95	92	88	85	92	89	86	83	86	84	81	79	81	79	77	75	68
3	4.31	3.95	10.0	97	95	92	90	94	92	90	87	89	87	85	83	83	81	80	78	71

