

屋内照明器具特性	
品番 (品名)	NNFS 4 2 2 3 0
光源	LDL40S . N / 19 / 25 - K ×2 2500.0 1 m
管理番号	K0128987 (1) DB 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	92 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	51	39	32	26	50	39	31	26	47	37	31	26	45	36	30	25	23	
		0.8	61	49	41	35	59	48	41	35	56	46	40	35	53	45	39	34	32	
		1.0	67	56	48	42	65	55	47	42	61	53	46	41	58	51	45	40	38	
		1.25	72	62	55	49	70	61	54	48	67	59	53	48	64	57	51	47	44	
下方投影面積	c m ²	1.5	76	67	60	54	74	66	59	54	71	63	57	53	67	61	56	52	49	
		2.0	82	74	67	62	80	73	66	61	76	70	65	60	73	67	63	59	56	
取付高さ	器具間隔最大限		2.5	85	78	73	68	83	77	72	67	80	74	70	66	76	72	68	64	61
	横方向 (A)	縦方向 (B)	3.0	88	82	76	72	86	80	75	71	82	78	73	70	79	75	71	68	65
1.5m	2.1 m	2.12 m	4.0	91	86	82	78	89	85	81	77	86	82	78	75	82	79	76	74	70
2	2.78	2.67	5.0	93	89	85	82	91	87	84	81	88	85	82	79	85	82	79	77	74
2.5	3.45	3.24	7.0	95	92	89	87	94	91	88	86	90	88	86	83	87	85	83	81	78
3	4.12	3.83	10.0	97	95	93	91	96	93	91	90	92	91	89	87	89	88	86	85	81

