

屋内照明器具特性

品番 (品名)	NNF W4 1 0 0 1				
光源	LDL40S . N / 14 / 26 (2600A) × 1 2600.0 1 m				
管理番号	K0133769 (2) DB 1				
BZ分類	BZ6				

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		21 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		77 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.83	0.6	49	37	29	23	47	35	28	23	42	32	26	21	38	30	24	20	17	
	中	0.81	0.8	58	46	38	32	55	44	36	31	50	41	34	29	45	37	32	27	23	
	否	0.77	1.0	64	52	44	38	61	50	43	37	55	46	40	35	50	42	37	32	28	
	下方投影面積	c m ²		1.25	70	59	51	45	66	56	49	43	60	52	46	41	54	48	42	38	33
等価発光面積	c m ²		1.5	74	64	56	50	70	61	54	48	64	56	50	45	58	51	46	42	37	
	c m ²		2.0	79	71	64	58	76	68	61	56	69	62	57	52	62	57	53	49	42	
取付高さ	器具間隔最大限		2.5	83	75	69	63	79	72	66	61	72	66	62	57	66	61	57	53	47	
	横方向 (A)	縦方向 (B)	3.0	85	79	73	68	82	76	70	66	75	70	65	61	68	64	60	57	50	
1.5m	2.21 m	2.14 m	4.0	89	83	78	74	85	80	75	71	78	74	70	67	71	68	65	62	55	
2	2.92	2.69	5.0	91	86	82	78	87	83	79	75	80	77	73	70	73	71	68	65	58	
2.5	3.62	3.27	7.0	94	90	86	83	90	86	83	80	83	80	77	75	76	74	72	70	62	
3	4.32	3.86	10.0	96	93	90	88	92	89	87	85	85	83	81	79	78	77	75	73	65	

