

屋内照明器具特性

品番 (品名)	NNF W4 1 0 2 1	
光源	LDL40S . N / 14 / 26 (2600A) × 1 2600 . 0 1 m	
管理番号	K0133636 (4) DB 1	
BZ分類	BZ6	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		21 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		72 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.83	0.6	4.6	3.5	2.7	2.2	4.4	3.3	2.6	2.1	4.0	3.1	2.5	2.0	3.6	2.8	2.3	1.9	1.6	
		0.81	0.8	5.5	4.3	3.6	3.0	5.2	4.2	3.4	2.9	4.7	3.8	3.2	2.7	4.2	3.5	3.0	2.6	2.2	
		0.77	1.0	6.1	5.0	4.2	3.6	5.8	4.8	4.0	3.5	5.2	4.4	3.8	3.3	4.7	4.0	3.5	3.1	2.6	
			1.25	6.6	5.6	4.8	4.2	6.3	5.3	4.6	4.1	5.7	4.9	4.3	3.8	5.1	4.5	4.0	3.6	3.1	
下方投影面積 等価発光面積	c m ²		1.5	7.0	6.0	5.3	4.7	6.6	5.8	5.1	4.6	6.0	5.3	4.7	4.3	5.4	4.9	4.4	4.0	3.4	
	c m ²		2.0	7.5	6.7	6.0	5.5	7.1	6.4	5.8	5.3	6.5	5.9	5.4	4.9	5.9	5.4	5.0	4.6	4.0	
	c m ²		2.5	7.8	7.1	6.5	6.0	7.5	6.8	6.3	5.8	6.8	6.3	5.8	5.4	6.2	5.8	5.4	5.0	4.4	
取付 高さ	器具間隔最大限		3.0	8.1	7.4	6.9	6.4	7.7	7.1	6.6	6.2	7.0	6.6	6.1	5.8	6.4	6.0	5.7	5.4	4.7	
	横方向 (A)	縦方向 (B)																			
1.5m	2.24 m	2.13 m	4.0	8.4	7.9	7.4	7.0	8.0	7.6	7.1	6.7	7.4	7.0	6.6	6.3	6.7	6.4	6.1	5.8	5.1	
2	2.95	2.68	5.0	8.6	8.1	7.7	7.4	8.2	7.8	7.5	7.1	7.6	7.2	6.9	6.6	6.9	6.6	6.4	6.2	5.4	
2.5	3.66	3.24	7.0	8.8	8.5	8.2	7.9	8.5	8.2	7.9	7.6	7.8	7.5	7.3	7.1	7.2	7.0	6.8	6.6	5.8	
3	4.37	3.83	10.0	9.0	8.8	8.5	8.3	8.7	8.4	8.2	8.0	8.0	7.8	7.6	7.4	7.4	7.2	7.1	6.9	6.1	

