

屋内照明器具特性	
品番 (品名)	NNF W4 1 0 2 1
光源	LDL40S . N / 29 / 31 - 9 (3150A) ×1 3150.0 1m
管理番号	K0125165 (5) DR 1
BZ分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 6.0 / BZ6

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	11 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	85 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.93	0.6	51	39	31	26	49	38	31	26	46	36	30	25	43	34	28	24	22
	中	0.9	0.8	60	49	41	35	58	47	40	34	54	45	38	33	50	43	37	32	29
	否	0.86	1.0	66	55	47	42	64	54	47	41	60	51	45	40	56	48	43	38	35
			1.25	72	62	54	48	69	60	53	48	65	57	51	46	60	54	49	45	41
下方投影面積			1.5	76	66	59	54	73	65	58	53	68	61	56	51	64	58	53	49	45
	等価発光面積		2.0	81	73	67	61	78	71	65	60	74	68	62	58	69	64	60	56	52
取付高さ	器具間隔最大限		2.5	85	78	72	67	82	76	70	66	77	72	67	63	72	68	64	61	56
	横方向 (A)	縦方向 (B)	3.0	87	81	76	71	84	79	74	70	79	75	71	67	75	71	68	64	60
1.5m	2.1m	2.09m	4.0	90	85	81	77	88	83	79	75	83	79	75	72	78	75	72	70	64
2	2.77	2.62	5.0	92	88	84	81	90	86	82	79	85	82	79	76	80	78	75	73	68
2.5	3.44	3.18	7.0	95	91	88	85	92	89	86	84	87	85	82	80	83	81	79	77	72
3	4.11	3.75	10.0	96	94	92	89	94	92	90	88	89	87	86	84	85	83	82	80	75

