

# 屋内照明器具特性

品番 (品名)	NNF W4 1 0 7 1 C									
光源	LDL40S . N / 29 / 31 - 9 ( 3150 A ) × 1					3150 . 0 1 m				
管理番号	K0125133 ( 3 ) DR 1									
B Z 分類	BZ6 / 0 . 7 / BZ5 / 3 . 5 / BZ6 / 4 . 5 / BZ5 / 6 . 0 / BZ6									

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		10 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		85 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0 . 01 )																			ZCM	
保守率	良	0 . 93	0 . 6	51	39	31	26	49	38	30	25	45	36	29	25	42	34	28	24	21	
	中	0 . 9	0 . 8	60	48	40	34	57	47	39	34	54	44	38	33	50	42	36	32	29	
	否	0 . 86	1 . 0	66	55	47	41	63	53	46	40	59	51	44	39	55	48	42	38	35	
	下方投影面積	c m <sup>2</sup>		1 . 25	71	61	54	48	69	60	53	47	64	56	50	46	60	54	48	44	40
等価発光面積	c m <sup>2</sup>		1 . 5	75	66	59	53	73	64	57	52	68	61	55	50	64	58	53	49	45	
	c m <sup>2</sup>		2 . 0	81	73	66	61	78	71	65	60	73	67	62	58	69	64	59	56	51	
取付高さ	器具間隔最大限		2 . 5	84	77	71	66	81	75	70	65	77	71	67	63	72	68	64	60	56	
	横方向 ( A )	縦方向 ( B )	3 . 0	86	80	75	70	84	78	73	69	79	74	70	67	74	71	67	64	59	
1 . 5m	2 . 12 m	2 . 1 m	4 . 0	90	85	80	76	87	83	78	75	82	78	75	72	78	75	72	69	64	
2	2 . 79	2 . 64	5 . 0	92	87	84	80	89	85	82	79	84	81	78	75	80	77	75	72	67	
2 . 5	3 . 46	3 . 2	7 . 0	94	91	88	85	92	89	86	83	87	84	82	80	82	80	78	77	71	
3	4 . 13	3 . 78	10 . 0	96	93	91	89	93	91	89	87	89	87	85	84	84	83	81	80	75	

