

屋内照明器具特性

品番 (品名)	NNF W4 2 0 0 1 K	
光源	LDL40S . N / 14 / 26 (2600A) × 2 2600.0 1 m	
管理番号	K0133768 (4) DB 1	
BZ分類	BZ6	

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	18 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	79 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	4.9	3.7	2.9	2.3	4.7	3.5	2.8	2.3	4.3	3.3	2.6	2.2	3.9	3.0	2.5	2.0	1.7			
	中	0.81	0.8	5.8	4.6	3.8	3.2	5.5	4.4	3.7	3.1	5.0	4.1	3.4	2.9	4.6	3.8	3.2	2.8	2.4			
	否	0.77	1.0	6.4	5.3	4.4	3.8	6.1	5.1	4.3	3.7	5.6	4.7	4.0	3.5	5.1	4.3	3.8	3.3	2.9			
			1.25	7.0	5.9	5.1	4.5	6.6	5.7	4.9	4.3	6.1	5.3	4.6	4.1	5.5	4.9	4.3	3.9	3.4			
下方投影面積		cm ²	1.5	7.4	6.4	5.6	5.0	7.0	6.1	5.4	4.8	6.4	5.7	5.1	4.6	5.9	5.3	4.8	4.3	3.8			
等価発光面積		cm ²	2.0	7.9	7.1	6.4	5.8	7.6	6.8	6.2	5.6	7.0	6.3	5.8	5.3	6.4	5.8	5.4	5.0	4.4			
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.7	6.2	7.3	6.7	6.2	5.8	6.7	6.2	5.8	5.5	4.9			
	横方向 (A)	縦方向 (B)	3.0	8.5	7.9	7.3	6.8	8.2	7.6	7.1	6.6	7.6	7.0	6.6	6.2	6.9	6.5	6.2	5.8	5.2			
1.5m	2.22 m	2.16 m	4.0	8.9	8.3	7.8	7.4	8.5	8.0	7.6	7.2	7.9	7.5	7.1	6.8	7.3	6.9	6.6	6.4	5.7			
2	2.92	2.71	5.0	9.1	8.6	8.2	7.8	8.8	8.3	7.9	7.6	8.1	7.8	7.4	7.1	7.5	7.2	6.9	6.7	6.0			
2.5	3.63	3.29	7.0	9.4	9.0	8.6	8.3	9.0	8.7	8.4	8.1	8.4	8.1	7.8	7.6	7.8	7.5	7.3	7.1	6.4			
3	4.33	3.88	10.0	9.6	9.3	9.0	8.8	9.2	9.0	8.7	8.5	8.6	8.4	8.2	8.0	8.0	7.8	7.7	7.5	6.8			

