

屋内照明器具特性	
品番 (品名)	NNF W4 2 0 2 1 K
光源	LDL40S . N / 29 / 31 - 9 (3150 A) × 2 3150.0 1 m
管理番号	K0125166 (3) DR 1
B Z 分類	BZ6 / 1.1 / BZ5 / 1.4 / BZ6

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 12 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	84 %	床		10 %				10 %				10 %				10 %				0 %			
室指数			照明率 (X0.01)																				ZCM
保守率	良	0.93	0.6	51	39	31	26	49	38	30	25	45	36	29	24	42	34	28	24	21			
	中	0.9	0.8	60	48	40	34	58	47	39	34	53	44	38	33	50	42	36	32	28			
	否	0.86	1.0	66	55	47	41	63	53	46	40	59	50	44	39	55	47	42	37	34			
			1.25	71	61	53	48	69	59	52	47	64	56	50	45	60	53	48	43	39			
下方投影面積	c m ²		1.5	75	66	58	53	73	64	57	52	68	60	55	50	63	57	52	48	44			
	等価発光面積		c m ²	2.0	81	73	66	60	78	71	64	59	73	67	61	57	68	63	58	55	50		
取付高さ	器具間隔最大限		2.5	84	77	71	66	81	75	69	65	76	71	66	62	71	67	63	59	54			
	横方向 (A)	縦方向 (B)	3.0	87	80	75	70	84	78	73	69	79	74	70	66	74	70	66	63	58			
1.5m	2.1 m	2.1 m	4.0	90	85	80	76	87	82	78	74	82	78	74	71	77	74	71	68	63			
2	2.77	2.63	5.0	92	88	84	80	89	85	81	78	84	81	78	75	79	76	74	71	66			
2.5	3.45	3.19	7.0	94	91	88	85	92	89	86	83	87	84	82	79	82	80	78	76	70			
3	4.11	3.76	10.0	96	94	91	89	94	91	89	87	89	87	85	83	84	82	81	79	73			

