

屋内照明器具特性

品番 (品名)	NNF W4 2 0 5 1 K				
光源	LDL40S.N/14/26(2600A) ×2 2600.0lm				
管理番号	K0134240(0)DB1				
BZ分類	BZ6				

器具効率	97%	天井	80%				70%				50%				30%				0%		
	上方光束		21%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		76%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.83	0.6	4.9	3.7	2.9	2.4	4.7	3.5	2.8	2.3	4.2	3.3	2.6	2.2	3.8	3.0	2.5	2.0	1.7	
	中	0.81	0.8	5.8	4.6	3.8	3.2	5.5	4.4	3.7	3.1	5.0	4.1	3.4	3.0	4.5	3.8	3.2	2.8	2.4	
	否	0.77	1.0	6.4	5.3	4.5	3.9	6.1	5.1	4.3	3.7	5.5	4.7	4.0	3.5	5.0	4.3	3.8	3.3	2.9	
	下方投影面積	c m ²		1.25	7.0	5.9	5.1	4.5	6.6	5.7	5.0	4.4	6.0	5.2	4.6	4.1	5.5	4.8	4.3	3.9	3.4
等価発光面積	c m ²		1.5	7.4	6.4	5.7	5.0	7.0	6.1	5.5	4.9	6.4	5.7	5.1	4.6	5.8	5.2	4.7	4.3	3.8	
	c m ²		2.0	7.9	7.1	6.4	5.9	7.6	6.8	6.2	5.7	6.9	6.3	5.8	5.3	6.3	5.8	5.4	5.0	4.4	
取付高さ	器具間隔最大限		2.5	8.3	7.6	6.9	6.4	7.9	7.3	6.7	6.2	7.3	6.7	6.2	5.8	6.6	6.2	5.8	5.5	4.8	
	横方向 (A)	縦方向 (B)	3.0	8.5	7.9	7.3	6.9	8.2	7.6	7.1	6.7	7.5	7.0	6.6	6.2	6.9	6.5	6.1	5.8	5.1	
1.5m	2.18m	2.15m	4.0	8.9	8.4	7.9	7.5	8.5	8.0	7.6	7.2	7.8	7.4	7.1	6.8	7.2	6.9	6.6	6.3	5.6	
2	2.88	2.71	5.0	9.1	8.6	8.2	7.9	8.7	8.3	8.0	7.6	8.0	7.7	7.4	7.1	7.4	7.1	6.9	6.7	5.9	
2.5	3.58	3.28	7.0	9.3	9.0	8.7	8.4	9.0	8.7	8.4	8.1	8.3	8.1	7.8	7.6	7.7	7.5	7.3	7.1	6.3	
3	4.27	3.88	10.0	9.5	9.3	9.0	8.8	9.2	9.0	8.7	8.5	8.5	8.3	8.1	8.0	7.9	7.7	7.6	7.4	6.6	

