

屋内照明器具特性	
品番 (品名)	NNF W4 2 0 5 1 K
光源	LDL40S . N / 29 / 31 - 9 (3150 A) × 2 3150.0 1 m
管理番号	K0125111 (0) DR 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 10 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	87 %	床		10 %				10 %				10 %				10 %				0 %			
室指数			照明率 (X0.01)																				ZCM
保守率	良	0.93	0.6	5.2	3.9	3.2	2.6	5.0	3.9	3.1	2.6	4.6	3.7	3.0	2.5	4.3	3.5	2.9	2.5	2.2			
	中	0.9	0.8	6.1	4.9	4.1	3.6	5.9	4.8	4.1	3.5	5.5	4.6	3.9	3.4	5.1	4.3	3.8	3.3	3.0			
	否	0.86	1.0	6.7	5.6	4.8	4.2	6.5	5.5	4.7	4.2	6.1	5.2	4.6	4.1	5.7	4.9	4.4	3.9	3.6			
			1.25	7.3	6.3	5.5	4.9	7.0	6.1	5.4	4.8	6.6	5.8	5.2	4.7	6.2	5.5	5.0	4.6	4.2			
下方投影面積	c m ²		1.5	7.7	6.8	6.0	5.5	7.4	6.6	5.9	5.4	7.0	6.3	5.7	5.2	6.5	5.9	5.5	5.0	4.7			
	等価発光面積		c m ²	2.0	8.2	7.4	6.8	6.3	8.0	7.3	6.7	6.2	7.5	6.9	6.4	6.0	7.1	6.6	6.1	5.8	5.3		
取付高さ	器具間隔最大限		2.5	8.6	7.9	7.3	6.8	8.3	7.7	7.2	6.7	7.9	7.3	6.9	6.5	7.4	7.0	6.6	6.3	5.8			
	横方向 (A)	縦方向 (B)	3.0	8.8	8.2	7.7	7.3	8.6	8.0	7.6	7.1	8.1	7.6	7.2	6.9	7.7	7.3	6.9	6.6	6.2			
1.5m	2.11 m	2.11 m	4.0	9.2	8.7	8.2	7.9	8.9	8.5	8.1	7.7	8.4	8.1	7.7	7.4	8.0	7.7	7.4	7.2	6.7			
2	2.78	2.65	5.0	9.4	9.0	8.6	8.2	9.1	8.7	8.4	8.1	8.6	8.3	8.1	7.8	8.2	8.0	7.7	7.5	7.0			
2.5	3.45	3.21	7.0	9.6	9.3	9.0	8.7	9.4	9.1	8.8	8.6	8.9	8.7	8.4	8.2	8.5	8.3	8.1	7.9	7.4			
3	4.12	3.78	10.0	9.8	9.6	9.3	9.1	9.6	9.3	9.1	9.0	9.1	8.9	8.8	8.6	8.7	8.5	8.4	8.3	7.7			

