

# 屋内照明器具特性

品番 (品名)	NNF W4 2 2 0 1 K														
光源	LDL40S.N/14/26(2600A) ×2      2600.0 1 m														
管理番号	K0125109(0)DR1														
BZ分類	BZ6/0.7/BZ5														

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	3 %	室指数	照明率 ( X0.01)																ZCM		
下方光束	92 %																				
保守率	良 中 否	0.81	0.6	5.2	4.0	3.2	2.7	5.0	3.9	3.2	2.6	4.7	3.8	3.1	2.6	4.5	3.6	3.0	2.6	2.4	
		0.77	0.8	6.1	4.9	4.1	3.6	5.9	4.8	4.1	3.5	5.6	4.7	4.0	3.5	5.3	4.5	3.9	3.5	3.2	
		0.68	1.0	6.7	5.6	4.8	4.2	6.5	5.5	4.8	4.2	6.2	5.3	4.7	4.2	5.9	5.1	4.6	4.1	3.8	
			1.25	7.3	6.3	5.5	4.9	7.1	6.1	5.4	4.9	6.7	5.9	5.3	4.8	6.4	5.7	5.2	4.7	4.5	
下方投影面積	c m <sup>2</sup>	1.5	7.7	6.7	6.0	5.5	7.5	6.6	6.0	5.4	7.1	6.4	5.8	5.3	6.8	6.2	5.7	5.2	5.0		
		2.0	8.2	7.4	6.8	6.3	8.0	7.3	6.7	6.2	7.6	7.0	6.5	6.1	7.3	6.8	6.4	6.0	5.7		
取付高さ	器具間隔最大限		2.5	8.6	7.9	7.3	6.8	8.4	7.7	7.2	6.8	8.0	7.5	7.0	6.6	7.7	7.2	6.8	6.5	6.2	
	横方向 (A)	縦方向 (B)	3.0	8.8	8.2	7.7	7.2	8.6	8.1	7.6	7.2	8.3	7.8	7.4	7.0	7.9	7.5	7.2	6.9	6.6	
1.5m	2.1 m	2.11 m	4.0	9.1	8.6	8.2	7.8	8.9	8.5	8.1	7.7	8.6	8.2	7.9	7.6	8.3	8.0	7.7	7.4	7.1	
2	2.77	2.65	5.0	9.3	8.9	8.5	8.2	9.1	8.8	8.4	8.1	8.8	8.5	8.2	7.9	8.5	8.2	8.0	7.8	7.4	
2.5	3.44	3.21	7.0	9.6	9.2	9.0	8.7	9.4	9.1	8.8	8.6	9.1	8.8	8.6	8.4	8.7	8.5	8.4	8.2	7.8	
3	4.1	3.79	10.0	9.7	9.5	9.3	9.1	9.6	9.4	9.2	9.0	9.3	9.1	8.9	8.7	9.0	8.8	8.7	8.5	8.2	

