

屋内照明器具特性	
品番 (品名)	NNF W4 2 2 2 1 K
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m
管理番号	K0125132(2)DR1
BZ分類	BZ6/0.7/BZ5

器具効率	91%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	88%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	49	38	30	25	48	37	30	25	45	36	29	25	43	35	29	25	22
	中	0.77	0.8	58	47	40	34	57	46	39	34	54	45	38	33	51	43	37	33	31
	否	0.68	1.0	64	54	46	40	62	53	46	40	59	51	44	40	56	49	43	39	37
			1.25	69	60	53	47	68	59	52	47	64	57	51	46	61	55	50	45	43
下方投影面積			1.5	73	64	58	52	71	63	57	52	68	61	55	51	65	59	54	50	47
			2.0	79	71	65	60	77	70	64	59	73	67	62	58	70	65	61	57	54
取付高さ	器具間隔最大限		2.5	82	75	70	65	80	74	69	65	77	72	67	63	73	69	65	62	59
	横方向 (A)	縦方向 (B)	3.0	84	79	74	69	82	77	73	69	79	75	71	67	76	72	69	66	63
1.5m	2.12 m	2.11 m	4.0	87	83	79	75	86	81	78	74	82	79	75	72	79	76	73	71	68
2	2.79	2.65	5.0	89	85	82	79	88	84	81	78	84	81	79	76	81	79	76	74	71
2.5	3.47	3.21	7.0	92	89	86	83	90	87	85	82	87	84	82	80	84	82	80	78	75
3	4.14	3.79	10.0	93	91	89	87	92	90	88	86	89	87	85	84	86	84	83	82	78

