

屋内照明器具特性

品番 (品名)	NNLK41509 + FSK41020 + NNL46														
光源	LED4000_85_4990 x1 4990.0 lm														
管理番号	K0139114 (3) DR1														
BZ分類	BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	15 %																			
下方光束	85 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.81 中 0.77 否 0.68	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20	
		0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27	
		1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33	
		1.25	73	62	54	48	70	60	52	47	65	56	50	45	60	53	47	43	38	
下方投影面積	c m ²	1.5	77	67	59	53	74	65	57	52	68	61	54	49	63	57	52	47	42	
		2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49	
取付高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	86	79	74	69	80	75	70	66	74	70	66	63	57
1.5m	1.67 m	2.16 m	4.0	92	87	82	77	89	84	79	75	83	79	75	72	78	74	71	68	62
2	2.21	2.72	5.0	94	90	85	81	91	87	83	79	85	82	79	75	80	77	74	72	65
2.5	2.74	3.3	7.0	97	93	90	87	94	91	87	84	88	85	83	80	83	80	78	76	70
3	3.28	3.9	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	82	80	73

