

# 屋内照明器具特性

|         |                        |            |
|---------|------------------------|------------|
| 品番 (品名) | NNLK41509 + NNL4000TNJ |            |
| 光源      | LED5000_85_10000 ×1    | 10000.0 lm |
| 管理番号    | K0159375 (0) D 1       |            |
| BZ分類    | BZ3 / 2.8 / BZ4        |            |

|        |                  |         |                  |               |     |     |      |      |     |    |      |      |    |    |      |      |    |    |     |     |  |  |  |
|--------|------------------|---------|------------------|---------------|-----|-----|------|------|-----|----|------|------|----|----|------|------|----|----|-----|-----|--|--|--|
| 器具効率   | 100 %            | 天井      | 80 %             |               |     |     | 70 % |      |     |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |  |  |  |
|        |                  |         | 壁                | 70            | 50  | 30  | 10   | 70   | 50  | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |  |  |  |
| 上方光束   | 3 %              | 反射率     | 床                | 10 %          |     |     |      | 10 % |     |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |  |  |  |
| 下方光束   | 97 %             |         | 室指数              | 照明率 ( X0.01 ) |     |     |      |      |     |    |      |      |    |    |      |      |    |    |     |     |  |  |  |
| 保守率    | 良                | 0.83    | 0.6              | 64            | 53  | 46  | 42   | 62   | 53  | 46 | 42   | 60   | 51 | 45 | 41   | 58   | 50 | 45 | 41  | 39  |  |  |  |
|        | 中                | 0.81    | 0.8              | 73            | 63  | 56  | 52   | 71   | 62  | 56 | 51   | 69   | 61 | 55 | 51   | 66   | 59 | 54 | 50  | 48  |  |  |  |
|        | 否                | 0.77    | 1.0              | 79            | 70  | 63  | 58   | 77   | 69  | 63 | 58   | 74   | 67 | 62 | 57   | 71   | 65 | 61 | 57  | 55  |  |  |  |
|        |                  |         | 1.25             | 84            | 76  | 70  | 65   | 82   | 75  | 69 | 65   | 79   | 73 | 68 | 64   | 76   | 71 | 67 | 63  | 61  |  |  |  |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 87            | 80  | 74  | 70   | 86   | 79  | 73 | 69   | 82   | 77 | 72 | 68   | 80   | 75 | 71 | 67  | 65  |  |  |  |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0           | 92  | 86  | 81   | 77   | 90  | 85 | 80   | 76   | 87 | 82 | 78   | 84   | 80 | 77 | 74  | 71  |  |  |  |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 95            | 90  | 85  | 81   | 93   | 88  | 84 | 81   | 90   | 86 | 82 | 79   | 87   | 83 | 80 | 78  | 75  |  |  |  |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 97            | 92  | 88  | 85   | 95   | 91  | 87 | 84   | 92   | 88 | 85 | 82   | 89   | 86 | 83 | 81  | 78  |  |  |  |
| 1.5m   | 1.11 m           | 2.6 m   | 4.0              | 99            | 96  | 92  | 89   | 98   | 94  | 91 | 88   | 94   | 92 | 89 | 87   | 91   | 89 | 87 | 85  | 82  |  |  |  |
| 2      | 1.51             | 3.37    | 5.0              | 101           | 98  | 95  | 92   | 99   | 96  | 94 | 91   | 96   | 94 | 91 | 89   | 93   | 91 | 89 | 88  | 84  |  |  |  |
| 2.5    | 1.89             | 4.16    | 7.0              | 103           | 100 | 98  | 96   | 101  | 99  | 97 | 95   | 98   | 96 | 94 | 93   | 95   | 94 | 92 | 91  | 87  |  |  |  |
| 3      | 2.25             | 4.96    | 10.0             | 104           | 102 | 101 | 99   | 102  | 101 | 99 | 98   | 99   | 98 | 97 | 96   | 96   | 95 | 94 | 93  | 90  |  |  |  |

