

屋内照明器具特性	
品番 (品名)	X F X 4 0 2 F E V
光源	LED3500_85_6140 ×1 6140.0 lm
管理番号	K0192932 (0) DB 1
B Z 分類	BZ2 / 2.3 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																	
保守率			良 中 否	0.81	0.6	68	58	51	47	66	57	51	47	64	56	51	47	63	55	50	47	45	
				0.77	0.8	78	70	64	60	77	69	64	60	75	68	63	60	73	67	63	59	58	
				0.68	1.0	85	78	72	68	84	77	72	68	82	76	71	68	79	74	70	67	66	
					1.25	90	84	79	75	89	83	78	75	86	81	77	74	84	80	77	74	72	
下方投影面積			cm ²	1.5	93	87	83	80	92	87	83	79	90	85	82	79	87	84	81	78	76		
				2.0	97	93	89	86	96	92	88	85	94	90	87	85	91	88	86	84	82		
等価発光面積			cm ²	2.5	100	96	93	90	98	95	92	89	96	93	91	88	94	91	89	87	85		
				3.0	101	98	95	93	100	97	94	92	98	95	93	91	95	93	91	90	88		
1.5m		2.18 m	2.05 m	4.0	103	100	98	96	102	99	97	96	99	98	96	94	97	96	94	93	91		
2		2.9	2.58	5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95	92		
2.5		3.62	3.14	7.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97	94		
3		4.33	3.71	10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96		

