

屋内照明器具特性	
品番 (品名)	X S Z B 1 0 2 5 0
光源	L L D 2 4 0 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 3 9 6 6 (0) D B 1
B Z 分類	B Z 1

器具効率		7 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 7	5 0	4 5	4 2	5 6	4 9	4 5	4 2	5 5	4 9	4 5	4 2	5 3	4 8	4 5	4 2	4 1
			0 . 6 3	0 . 8	6 4	5 8	5 4	5 1	6 3	5 8	5 4	5 1	6 2	5 7	5 4	5 1	6 0	5 6	5 3	5 1	5 0
			0 . 5 6	1 . 0	6 9	6 4	6 0	5 7	6 8	6 3	6 0	5 7	6 6	6 2	5 9	5 7	6 5	6 1	5 8	5 6	5 5
				1 . 2 5	7 2	6 8	6 4	6 2	7 1	6 7	6 4	6 2	7 0	6 6	6 3	6 1	6 8	6 5	6 3	6 1	6 0
下方投影面積		c m ²	1 . 5	7 5	7 1	6 8	6 5	7 4	7 0	6 7	6 5	7 2	6 9	6 6	6 4	7 0	6 8	6 6	6 4	6 2	
			2 . 0	7 7	7 4	7 2	6 9	7 7	7 4	7 1	6 9	7 5	7 2	7 0	6 8	7 3	7 1	6 9	6 8	6 6	
等価発光面積	c m ²	2 . 5	7 9	7 6	7 4	7 2	7 8	7 6	7 4	7 2	7 6	7 4	7 3	7 1	7 5	7 3	7 2	7 0	6 9		
		3 . 0	8 0	7 8	7 6	7 4	7 9	7 7	7 5	7 4	7 8	7 6	7 4	7 3	7 6	7 4	7 3	7 2	7 0		
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	8 2	8 0	7 8	7 7	8 1	7 9	7 8	7 6	7 9	7 8	7 6	7 5	7 7	7 6	7 5	7 4	7 2	
			5 . 0	8 2	8 1	8 0	7 8	8 1	8 0	7 9	7 8	8 0	7 9	7 8	7 7	7 8	7 7	7 6	7 5	7 4	
			7 . 0	8 3	8 2	8 1	8 0	8 2	8 1	8 0	8 0	8 1	8 0	7 9	7 8	7 9	7 8	7 8	7 7	7 5	
			1 0 . 0	8 4	8 3	8 2	8 2	8 3	8 2	8 2	8 1	8 1	8 1	8 0	8 0	8 0	7 9	7 9	7 8	7 6	

