

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X439 KHW                  |
| 光源       | LED4000_85_3010 ×1 3010.0 lm |
| 管理番号     | K0192151 ( 0 ) D 1           |
| BZ分類     | BZ5/2.8/BZ4                  |

| 器具効率<br><br>上方光束<br>下方光束 |           | 100 %<br><br>1 %<br><br>99 %           |           | 反射率  | 天井  | 80 %              |     |    |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------------------------|-----------|----------------------------------------|-----------|------|-----|-------------------|-----|----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|                          |           |                                        |           |      | 壁   | 70                | 50  | 30 | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                          |           |                                        |           |      | 床   | 10 %              |     |    |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                          |           |                                        |           |      | 室指数 | 照明率 ( X0.01 ) ZCM |     |    |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率                      |           | 良<br>中<br>否                            | 0.81      | 0.6  | 57  | 45                | 37  | 32 | 56  | 44   | 37  | 32 | 53  | 43   | 36 | 31 | 51 | 42   | 36 | 31 | 29 |     |
|                          |           |                                        | 0.77      | 0.8  | 67  | 56                | 48  | 42 | 66  | 55   | 47  | 42 | 63  | 53   | 47 | 42 | 60 | 52   | 46 | 41 | 39 |     |
|                          |           |                                        | 0.68      | 1.0  | 74  | 63                | 55  | 50 | 72  | 62   | 55  | 50 | 69  | 61   | 54 | 49 | 66 | 59   | 53 | 49 | 46 |     |
|                          |           |                                        |           | 1.25 | 80  | 70                | 63  | 57 | 78  | 69   | 62  | 57 | 75  | 67   | 61 | 57 | 72 | 66   | 60 | 56 | 54 |     |
| 下方投影面積<br>等価発光面積         |           | cm <sup>2</sup><br><br>cm <sup>2</sup> |           | 1.5  | 84  | 75                | 68  | 63 | 82  | 74   | 68  | 63 | 79  | 72   | 67 | 62 | 76 | 70   | 65 | 61 | 59 |     |
|                          |           |                                        | 2.0       | 90   | 82  | 76                | 72  | 88 | 81  | 76   | 71  | 85 | 79  | 74   | 70 | 82 | 77 | 73   | 69 | 67 |    |     |
| 取付<br>高さ                 | 器具間隔最大限   |                                        |           | 2.5  | 93  | 87                | 82  | 77 | 91  | 86   | 81  | 77 | 88  | 84   | 79 | 76 | 86 | 81   | 78 | 75 | 72 |     |
|                          | 横方向 ( A ) |                                        | 縦方向 ( B ) | 3.0  | 96  | 90                | 86  | 82 | 94  | 89   | 85  | 81 | 91  | 87   | 83 | 80 | 88 | 85   | 82 | 79 | 76 |     |
| 1.5m                     | 1.94 m    | 2.11 m                                 |           | 4.0  | 99  | 95                | 91  | 87 | 97  | 93   | 90  | 87 | 94  | 91   | 88 | 85 | 92 | 89   | 86 | 84 | 81 |     |
| 2                        | 2.56      | 2.66                                   |           | 5.0  | 101 | 97                | 94  | 91 | 99  | 96   | 93  | 90 | 96  | 94   | 91 | 89 | 94 | 91   | 89 | 87 | 84 |     |
| 2.5                      | 3.18      | 3.22                                   |           | 7.0  | 103 | 100               | 98  | 96 | 101 | 99   | 97  | 95 | 99  | 97   | 95 | 93 | 96 | 94   | 93 | 91 | 88 |     |
| 3                        | 3.8       | 3.81                                   |           | 10.0 | 104 | 103               | 101 | 99 | 103 | 101  | 100 | 98 | 100 | 99   | 98 | 96 | 98 | 97   | 95 | 94 | 91 |     |

