

屋内照明器具特性	
品番 (品名)	S L B 8 0 5 8 1
光源	LED2700_70_130 ×1 130.0 l m
管理番号	K0147468 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ6

器具効率	100 % 上方光束 50 % 下方光束 50 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X0.01) Z C M																
保守率	良 0.63	0.6	49	38	30	25	45	35	28	24	38	30	25	21	32	25	21	18	13
	中 0.6	0.8	57	46	38	33	53	43	36	31	44	37	31	27	36	31	26	23	17
	否 0.56	1.0	63	52	45	39	58	48	42	36	48	41	36	32	40	34	30	27	19
		1.25	68	58	51	45	63	54	47	42	52	46	41	36	43	38	34	31	22
下方投影面積 等価発光面積	c m ²	1.5	72	63	55	50	66	58	52	46	55	49	44	40	46	41	37	34	24
		2.0	77	69	62	57	71	64	58	53	60	54	50	46	49	45	42	39	27
		2.5	80	73	67	62	74	68	63	58	62	58	54	50	52	48	45	42	30
取付高さ	器具間隔最大限		3.0	83	76	71	66	76	71	66	62	64	60	56	53	53	50	47	32
	横方向 (A)	縦方向 (B)	4.0	86	81	76	72	79	75	71	67	67	64	61	58	56	53	51	35
H m	0.65 H m	1.49 H m	5.0	88	83	79	76	81	77	74	71	69	66	63	61	57	55	53	37
			7.0	90	87	83	80	84	81	78	75	71	69	67	65	59	58	56	39
			10.0	92	89	87	85	85	83	81	79	73	71	69	68	61	60	58	41

