

屋内照明器具特性

品番 (品名)

S L D 1 0 3 8 V

光源

L E D 3 5 0 0 _ 7 0 _ 1 6 1 × 1 1 6 1 . 0 l m

管理番号

K 0 1 4 7 6 3 9 (0) D B 1

B Z 分類

B Z 1

器具効率

1 0 2 %

上方光束

0 %

下方光束

1 0 2 %

天井
壁
床

8 0 %

7 0 %

5 0 %

3 0 %

0 %

7 0 5 0 3 0 1 0 7 0 5 0 3 0 1 0 7 0 5 0 3 0 1 0 7 0 5 0 3 0 1 0

1 0 %

1 0 %

1 0 %

1 0 %

0 %

室指数

照明率 (× 0 . 0 1)

Z C M

保守率

良 0 . 6 7

中 0 . 6 3

否 0 . 5 6

下方投影面積

c m ²

等価発光面積

c m ²

取付

器具間隔最大限

高さ

横方向 (A)

縦方向 (B)

H m

0 . 5 0 H m

0 . 5 0 H m

0 . 6	9 1	8 6	8 3	8 1	9 1	8 6	8 3	8 1	9 0	8 6	8 3	8 1	8 9	8 5	8 3	8 1	8 0
0 . 8	9 6	9 2	8 9	8 7	9 5	9 1	8 9	8 7	9 4	9 1	8 8	8 6	9 3	9 0	8 8	8 6	8 5
1 . 0	9 9	9 5	9 2	9 0	9 8	9 5	9 2	9 0	9 7	9 4	9 1	9 0	9 5	9 3	9 1	8 9	8 8
1 . 2 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 3	9 9	9 6	9 4	9 3	9 7	9 5	9 3	9 2	9 1
1 . 5	1 0 3	1 0 0	9 7	9 6	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 6	9 5	9 9	9 7	9 5	9 4	9 2
2 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 4	1 0 1	1 0 0	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 9	9 7	9 6	9 5
2 . 5	1 0 6	1 0 4	1 0 2	1 0 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 6
3 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 7
4 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	9 8
5 . 0	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	9 9
7 . 0	1 0 8	1 0 8	1 0 7	1 0 6	1 0 7	1 0 7	1 0 6	1 0 5	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	9 9
1 0 . 0	1 0 9	1 0 8	1 0 8	1 0 7	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 3	1 0 0

配光曲線

ランプ光束 1 0 0 0 l m

— 管軸に垂直 (A)
- - - 管軸に平行 (B)

直射水平面照度

ランプ光束 1 0 0 0 l m

8 0 lx X 1 0 0

6 0

4 0

2 0

H = 1 . 5

H = 2

H = 2 . 5

H = 3

H = 4

H = 5

1 0

6

4

2

1

0 . 8

0 . 6

0 . 4

0 . 2

8 m 6 4 2 0 2 4 6 8