

# 屋内照明器具特性

品番 (品名)	NNFJ 4 2 5 7 6 K														
光源	LDL40S . N / 29 / 31 - 9 ( 3150 A ) × 2      3150.0 1 m														
管理番号	K0126944 ( 0 ) DB 1														
B Z 分類	B Z 5														

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	88 %	室指数	照明率 ( X0.01 )      ZCM																	
保守率	良 中 否	0.86	0.6	51	39	32	27	49	39	31	26	47	37	31	26	44	36	30	26	23
		0.81	0.8	60	49	42	36	58	48	41	36	55	46	40	35	52	45	39	35	32
			1.0	66	56	49	43	64	55	48	43	61	53	47	42	58	51	45	41	38
		0.76	1.25	72	62	55	50	70	61	55	49	66	59	53	48	63	57	52	47	45
下方投影面積	c m <sup>2</sup>	1.5	76	67	60	55	74	66	60	55	70	63	58	53	67	61	56	52	49	
		2.0	81	74	68	63	79	72	67	62	75	70	65	61	72	67	63	59	56	
取付高さ	器具間隔最大限		2.5	84	78	73	68	82	77	72	68	79	74	70	66	75	71	67	64	61
	横方向 ( A )	縦方向 ( B )	3.0	87	81	77	72	85	80	75	72	81	77	73	70	77	74	71	68	64
1.5m	2.16 m	2.17 m	4.0	90	85	81	78	88	84	80	77	84	81	78	75	81	78	75	73	69
2	2.85	2.72	5.0	92	88	85	81	90	86	83	80	86	83	81	78	83	80	78	76	72
2.5	3.55	3.3	7.0	94	91	88	86	92	89	87	85	88	86	84	82	85	83	81	80	76
3	4.24	3.87	10.0	95	93	91	89	94	92	90	88	90	88	87	85	87	85	84	83	79

