

屋内照明器具特性	
品番 (品名)	NNLK42123 + NEL4400EN
光源	LED5000_85_4000 ×1 4000.0 lm
管理番号	K0192925 (0) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.83	0.6	56	43	35	30	54	43	35	30	51	41	34	29	49	40	34	29	27	
			0.81	0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	39	36	
			0.77	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
				1.25	78	68	60	54	76	66	59	54	72	64	58	53	69	62	57	52	49	
下方投影面積		cm ²		1.5	82	73	65	60	80	71	65	59	76	69	63	58	73	66	61	57	54	
				2.0	87	80	73	68	85	78	72	67	82	75	70	66	78	73	69	65	62	
等価発光面積		cm ²		2.5	91	84	78	74	89	83	77	73	85	80	75	71	82	77	73	70	67	
				3.0	93	87	82	78	91	86	81	77	88	83	79	75	84	80	77	74	70	
1.5m		1.97 m	2.13 m		4.0	97	92	88	84	95	90	86	83	91	87	84	81	88	84	82	79	75
2		2.6	2.67		5.0	99	95	91	88	97	93	90	86	93	90	87	84	90	87	85	82	79
2.5		3.23	3.23		7.0	101	98	95	92	99	96	94	91	96	93	91	89	92	90	88	87	83
3		3.86	3.81		10.0	103	100	98	96	101	99	97	95	98	96	94	92	94	93	91	90	86

