

屋内照明器具特性	
品番 (品名)	NNLK42591J + NEL4500HN
光源	LED5000_85_4560 ×1 4560.0 lm
管理番号	K0192610 (0) DB 1
BZ分類	BZ4 / 0.9 / BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		4 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		96 %																					
保守率		良 中 否	0.81	0.6	60	49	42	37	59	48	41	36	56	47	41	36	54	46	40	36	34		
			0.77	0.8	70	60	53	48	69	59	52	47	66	57	51	47	63	56	51	46	44		
			0.68	1.0	77	67	61	56	75	66	60	55	72	65	59	55	69	63	58	54	51		
				1.25	83	74	68	63	81	73	67	63	78	71	66	62	75	69	65	61	58		
下方投影面積		cm ²		1.5	87	79	73	68	85	78	72	68	81	75	71	67	78	73	69	66	63		
				2.0	92	85	80	76	90	84	79	75	86	82	78	74	83	79	76	73	70		
等価発光面積		cm ²		2.5	95	89	85	81	93	88	84	80	90	85	82	79	86	83	80	77	74		
				3.0	97	92	88	85	95	91	87	84	92	88	85	82	88	86	83	81	77		
1.5m		1.83 m	2.16 m		4.0	99	96	93	90	98	94	92	89	94	92	89	87	91	89	87	85	82	
2		2.42	2.71		5.0	101	98	95	93	99	97	94	92	96	94	92	90	93	91	89	88	84	
2.5		3.01	3.29		7.0	103	101	99	97	101	99	97	96	98	96	95	93	95	94	92	91	87	
3		3.6	3.88		10.0	104	103	101	100	103	101	100	99	99	98	97	96	96	95	94	94	90	

