

屋内照明器具特性	
品番 (品名)	NNN12310K
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0172938(0)DB1
BZ分類	BZ9

器具効率	71%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	31%	室指数	床	10%				10%				10%				10%				0%	
下方光束	40%		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.5	1.2	2.4	1.8	1.3	1.0	2.0	1.4	1.1	0.8	0.5	
	中 0.6		0.8	3.8	2.9	2.2	1.8	3.5	2.6	2.1	1.7	2.9	2.2	1.8	1.4	2.4	1.8	1.5	1.2	0.7	
	否 0.56		1.0	4.2	3.3	2.7	2.2	3.8	3.1	2.5	2.0	3.2	2.6	2.1	1.7	2.6	2.1	1.8	1.5	0.9	
			1.25	4.6	3.7	3.1	2.6	4.2	3.5	2.9	2.5	3.5	2.9	2.5	2.1	2.9	2.4	2.1	1.8	1.2	
下方投影面積	cm <sup>2</sup>	1.5	4.9	4.1	3.5	3.0	4.5	3.8	3.2	2.8	3.8	3.2	2.8	2.4	3.1	2.7	2.3	2.0	1.4		
等価発光面積		2.0	5.3	4.6	4.0	3.6	4.9	4.3	3.8	3.3	4.1	3.6	3.2	2.9	3.4	3.0	2.7	2.4	1.7		
取付高さ		器具間隔最大限		2.5	5.5	4.9	4.4	4.0	5.1	4.6	4.1	3.7	4.3	3.9	3.5	3.2	3.6	3.3	3.0	2.7	1.9
Hm		1.85Hm	縦方向(B)	3.0	5.7	5.2	4.7	4.3	5.3	4.8	4.4	4.0	4.5	4.1	3.8	3.5	3.8	3.5	3.2	3.0	2.1
		横方向(A)	4.0	6.0	5.5	5.1	4.8	5.6	5.2	4.8	4.5	4.8	4.4	4.1	3.9	4.0	3.7	3.5	3.3	2.4	
			5.0	6.2	5.8	5.4	5.1	5.7	5.4	5.1	4.8	4.9	4.6	4.4	4.1	4.2	3.9	3.7	3.5	2.6	
			7.0	6.4	6.1	5.8	5.5	5.9	5.7	5.4	5.2	5.1	4.9	4.7	4.5	4.3	4.2	4.0	3.8	2.9	
			10.0	6.5	6.3	6.1	5.9	6.1	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.5	4.4	4.2	4.1	3.1	

