

# 屋内照明器具特性

品番 (品名)	NNN17510K+NNN89992K	
光源	LED5000_80_4415 ×1      4415.0 lm	
管理番号	K0153647(0)DB1	
BZ分類	BZ1/4.5/BZ2/6.0/BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.76	0.6	77	70	65	62	77	70	65	62	75	69	65	62	74	68	64	61	60
	中	0.72	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67
	否	0.64	1.0	88	82	77	74	87	81	77	74	85	80	76	74	83	79	76	73	72
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	92	86	82	79	91	86	82	79	89	84	81	78	87	83	80	78	76
			1.5	94	89	85	82	93	89	85	82	91	87	84	81	89	86	83	81	79
取付高さ	器具間隔最大限		2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	93	98	95	93	91	96	94	92	90	88
Hm	0.85Hm	0.83Hm	4.0	103	100	98	96	102	99	98	96	99	98	96	94	97	96	94	93	91
			5.0	104	102	100	99	103	101	99	98	100	99	98	96	98	97	96	95	92
			7.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	94
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	100	99	99	96

