

屋内照明器具特性

品番 (品名)	NNN17512K+NNN89990										
光源	LED3500_80_5205 x1 5205.0 lm										
管理番号	K0150638(0)DB1										
BZ分類	BZ1/1.8/BZ2										

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 97%	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.76	0.6	74	65	60	57	73	65	60	56	71	64	59	56	69	63	59	56	54	
	中 0.72	0.8	81	74	68	65	80	73	68	65	78	72	67	64	76	70	67	64	62	
	否 0.64	1.0	86	79	74	70	85	78	74	70	82	77	73	70	80	75	72	69	67	
	下方投影面積	1.25	90	84	79	76	88	83	79	75	86	81	77	74	84	80	76	74	72	
等価発光面積	cm ²	1.5	93	87	83	79	91	86	82	79	88	84	81	78	86	82	79	77	75	
	cm ²	2.0	96	91	88	85	95	90	87	84	92	88	85	83	89	86	84	82	79	
取付高さ	器具間隔最大限		2.5	98	94	91	88	97	93	90	87	94	91	88	86	91	89	87	85	82
	横方向 (A)	縦方向 (B)	3.0	100	96	93	91	98	95	92	90	95	93	90	88	93	91	89	87	84
Hm	0.95Hm	0.94Hm	4.0	102	99	96	94	100	98	95	93	97	95	93	92	95	93	91	90	87
			5.0	103	100	98	97	101	99	97	96	98	97	95	94	96	94	93	92	89
			7.0	104	102	101	99	103	101	100	98	100	98	97	96	97	96	95	94	91
			10.0	105	104	103	102	104	102	101	100	101	100	99	98	98	97	96	96	92

