

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 3 2 8
光源	LLD2401LCB1 ×1 500.0 l m
管理番号	K0193687 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3 / 0.9 / BZ4 / 6.0 / BZ5

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	11 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	78 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	53	43	37	33	51	42	36	32	48	41	35	32	45	39	34	31	28			
	中	0.6	0.8	61	52	46	41	59	51	45	41	56	49	44	40	53	47	42	39	36			
	否	0.56	1.0	67	58	52	48	65	57	51	47	61	54	49	46	57	52	48	44	41			
			1.25	71	64	58	53	69	62	57	53	65	59	55	51	61	56	53	49	46			
下方投影面積			1.5	75	68	62	58	72	66	61	57	68	63	58	55	64	60	56	53	49			
			2.0	79	73	68	64	77	71	67	63	72	68	64	61	68	64	61	59	54			
取付高さ	器具間隔最大限		2.5	82	76	72	68	79	75	71	67	75	71	68	65	70	67	65	62	58			
	横方向 (A)	縦方向 (B)	3.0	83	79	75	72	81	77	73	70	77	73	70	68	72	70	67	65	60			
H m	1.05 H m	0.49 H m	4.0	86	82	79	76	83	80	77	75	79	76	74	72	75	72	70	69	64			
			5.0	87	84	82	79	85	82	80	77	80	78	76	74	76	74	73	71	66			
			7.0	89	87	85	83	87	85	83	81	82	80	79	77	78	76	75	74	69			
			10.0	90	89	87	86	88	87	85	84	84	82	81	80	79	78	77	76	71			

