

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 1 8 3
光源	LLD2411VCB1 ×1 500.0 lm
管理番号	K0193247 (3) DB 1
B Z 分類	BZ1 / 0.9 / BZ2 / 2.8 / BZ3

器具効率		87 % 上方光束 14 % 下方光束 73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	0.6	59	51	46	43	57	50	46	42	54	48	44	42	52	47	43	41	38
			0.6	0.8	65	58	53	50	64	57	52	49	60	55	51	48	57	52	49	46	44	
			0.56	1.0	70	63	58	54	68	61	57	54	64	59	55	52	60	56	53	50	47	
				1.25	73	67	63	59	71	66	61	58	67	62	59	56	63	60	57	54	51	
下方投影面積 等価発光面積		cm ² cm ²	1.5	76	70	66	62	74	69	65	61	69	65	62	59	65	62	59	57	53		
			2.0	79	75	71	68	77	73	69	66	72	69	66	64	68	65	63	61	57		
			2.5	81	77	74	71	79	75	72	69	74	71	69	67	70	68	66	64	59		
			3.0	83	79	76	74	80	77	74	72	76	73	71	69	71	69	67	66	61		
H _m	0.77H _m		0.77H _m		4.0	85	82	79	77	82	80	77	75	77	75	73	72	73	71	70	68	63
					5.0	86	84	81	79	83	81	79	77	79	77	75	74	74	73	71	70	64
				7.0	87	86	84	82	85	83	82	80	80	79	77	76	75	74	73	72	66	
				10.0	88	87	86	85	86	85	83	82	81	80	79	78	76	75	75	74	68	

