

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 3 6 7
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0193060 (0) DB 1
B Z 分類	BZ6

器具効率		8 2 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		2 5 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		5 7 %																							
保守率		良 中 否	0 . 6 3	0 . 6	4 2	3 2	2 6	2 1	4 0	3 1	2 5	2 1	3 5	2 8	2 3	1 9	3 1	2 5	2 1	1 8	1 5				
			0 . 6	0 . 8	4 9	3 9	3 3	2 8	4 6	3 7	3 1	2 7	4 1	3 4	2 9	2 5	3 6	3 1	2 6	2 3	1 9				
			0 . 5 6	1 . 0	5 4	4 4	3 8	3 3	5 1	4 2	3 6	3 2	4 5	3 8	3 3	2 9	4 0	3 4	3 0	2 7	2 2				
				1 . 2 5	5 8	5 0	4 3	3 8	5 5	4 7	4 1	3 7	4 9	4 2	3 8	3 4	4 3	3 8	3 4	3 1	2 6				
下方投影面積		cm ²	1 . 5	6 1	5 3	4 7	4 2	5 8	5 1	4 5	4 1	5 1	4 6	4 1	3 7	4 6	4 1	3 7	3 4	2 8					
等価発光面積		cm ²	2 . 0	6 6	5 9	5 3	4 8	6 2	5 6	5 1	4 6	5 5	5 0	4 6	4 3	4 9	4 5	4 2	3 9	3 2					
取付 高さ	器具間隔最大限		2 . 5	6 8	6 2	5 7	5 3	6 5	5 9	5 5	5 1	5 8	5 4	5 0	4 6	5 2	4 8	4 5	4 2	3 5					
	横方向 (A)		縦方向 (B)	3 . 0	7 1	6 5	6 0	5 6	6 7	6 2	5 8	5 4	6 0	5 6	5 2	4 9	5 3	5 0	4 7	4 5	3 8				
H m	0 . 9 4 H m	0 . 9 4 H m	4 . 0	7 3	6 9	6 5	6 1	7 0	6 5	6 2	5 9	6 2	5 9	5 6	5 4	5 6	5 3	5 1	4 9	4 1					
			5 . 0	7 5	7 1	6 8	6 4	7 1	6 8	6 5	6 2	6 4	6 1	5 9	5 6	5 7	5 5	5 3	5 1	4 3					
			7 . 0	7 7	7 4	7 1	6 9	7 3	7 1	6 8	6 6	6 6	6 4	6 2	6 0	5 9	5 8	5 6	5 4	4 6					
			1 0 . 0	7 9	7 6	7 4	7 2	7 5	7 3	7 1	6 9	6 8	6 6	6 5	6 3	6 1	6 0	5 8	5 7	4 8					

