

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 3 7 9
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0193687 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3 / 0.9 / BZ4 / 6.0 / BZ5

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.63	0.6	53	43	37	33	51	42	36	32	48	41	35	32	45	39	34	31	28	
			0.6	0.8	61	52	46	41	59	51	45	41	56	49	44	40	53	47	42	39	36	
			0.56	1.0	67	58	52	48	65	57	51	47	61	54	49	46	57	52	48	44	41	
			1.25	71	64	58	53	69	62	57	53	65	59	55	51	61	56	53	49	46		
下方投影面積		cm ²	1.5	75	68	62	58	72	66	61	57	68	63	58	55	64	60	56	53	49		
			2.0	79	73	68	64	77	71	67	63	72	68	64	61	68	64	61	59	54		
取付 高さ	器具間隔最大限		2.5	82	76	72	68	79	75	71	67	75	71	68	65	70	67	65	62	58		
	横方向 (A)		縦方向 (B)		3.0	83	79	75	72	81	77	73	70	77	73	70	68	72	70	67	65	60
H m	1.05 H m		0.49 H m		4.0	86	82	79	76	83	80	77	75	79	76	74	72	75	72	70	69	64
					5.0	87	84	82	79	85	82	80	77	80	78	76	74	76	74	73	71	66
					7.0	89	87	85	83	87	85	83	81	82	80	79	77	78	76	75	74	69
					10.0	90	89	87	86	88	87	85	84	84	82	81	80	79	78	77	76	71

