

屋内照明器具特性	
品番 (品名)	L G D 1 3 0 4 V
光源	LED3500_70_465 ×1 465.0 l m
管理番号	K0190568 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3 / 1.1 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 6 7	0 . 6	6 2	5 0	4 3	3 8	6 0	5 0	4 3	3 8	5 8	4 9	4 3	3 8	5 6	4 8	4 2	3 8	3 6	
			0 . 6 3	0 . 8	7 1	6 1	5 4	4 9	7 0	6 0	5 4	4 9	6 7	5 9	5 3	4 8	6 5	5 8	5 2	4 8	4 6	
			0 . 5 6	1 . 0	7 8	6 8	6 1	5 6	7 6	6 7	6 1	5 6	7 3	6 6	6 0	5 6	7 1	6 4	5 9	5 5	5 3	
				1 . 2 5	8 3	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 3	7 6	7 1	6 6	6 2	6 0	
下方投影面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 3	6 8	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 7	6 5		
等価発光面積			c m ²	2 . 0	9 2	8 6	8 0	7 6	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 2	
取付高さ	器具間隔最大限			2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 4	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 7	
H m		1 . 0 9 H m	縦方向 (B)	3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	8 9	8 6	8 3	9 1	8 8	8 5	8 2	8 0	
H m		1 . 0 9 H m		4 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 1	8 8	9 3	9 1	8 9	8 7	8 4	
				5 . 0	1 0 2	9 9	9 6	9 3	1 0 0	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7	
				7 . 0	1 0 4	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 7	9 6	9 5	9 3	9 0	
				1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3	

