

屋内照明器具特性	
品番 (品名)	S L D 9 0 2 5
光源	L L D 2 4 0 0 L C B 1 × 1 5 0 0 . 0 1 m
管理番号	K 0 1 9 2 0 2 7 (0) D B 1
B Z 分類	B Z 1

器具効率		6 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 9	4 6	4 3	5 3	4 8	4 5	4 3	5 2	4 8	4 5	4 3	5 1	4 7	4 5	4 3	4 2
			0 . 6 3	0 . 8	5 9	5 4	5 2	5 0	5 8	5 4	5 1	4 9	5 7	5 4	5 1	4 9	5 6	5 3	5 1	4 9	4 8
			0 . 5 6	1 . 0	6 2	5 8	5 6	5 4	6 1	5 8	5 5	5 3	6 0	5 7	5 5	5 3	5 9	5 6	5 4	5 3	5 2
				1 . 2 5	6 4	6 1	5 9	5 7	6 4	6 1	5 8	5 7	6 2	6 0	5 8	5 6	6 1	5 9	5 7	5 6	5 5
下方投影面積		c m ²	1 . 5	6 6	6 3	6 1	5 9	6 5	6 3	6 0	5 9	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 8	5 7	
			等価発光面積	2 . 0	6 8	6 5	6 4	6 2	6 7	6 5	6 3	6 2	6 6	6 4	6 2	6 1	6 4	6 3	6 2	6 1	5 9
取付 高さ	器具間隔最大限		2 . 5	6 9	6 7	6 5	6 4	6 8	6 6	6 5	6 4	6 7	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 1	
	横方向 (A) 縦方向 (B)		3 . 0	7 0	6 8	6 7	6 5	6 9	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 2	
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	7 0	6 9	6 8	6 7	7 0	6 9	6 8	6 7	6 8	6 7	6 7	6 6	6 7	6 6	6 5	6 5	6 3	
			5 . 0	7 1	7 0	6 9	6 8	7 0	6 9	6 9	6 8	6 9	6 8	6 7	6 7	6 7	6 7	6 6	6 6	6 4	
			7 . 0	7 2	7 1	7 0	7 0	7 1	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 8	6 8	6 7	6 7	6 5	
			1 0 . 0	7 2	7 2	7 1	7 1	7 1	7 1	7 0	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 8	6 8	6 6	

