

屋内照明器具特性	
品番 (品名)	S L D 9 0 3 6
光源	L L D 3 4 0 1 L C B 1 × 1 7 0 0 . 0 1 m
管理番号	K 0 1 9 2 0 4 8 (0) D B 1
B Z 分類	B Z 1

器具効率		5 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		5 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 9	3 7	3 5	4 3	3 9	3 7	3 5	4 2	3 9	3 6	3 5	4 2	3 8	3 6	3 5	3 4	
			0 . 6 3	0 . 8	4 9	4 5	4 2	4 0	4 8	4 5	4 2	4 0	4 7	4 4	4 2	4 0	4 6	4 3	4 2	4 0	3 9	
			1 . 0	5 1	4 8	4 6	4 4	5 1	4 8	4 6	4 4	5 0	4 7	4 5	4 4	4 9	4 7	4 5	4 4	4 3		
			0 . 5 6	1 . 2 5	5 4	5 1	4 9	4 7	5 3	5 0	4 8	4 7	5 2	5 0	4 8	4 7	5 1	4 9	4 8	4 6	4 5	
下方投影面積		c m ²	1 . 5	5 5	5 3	5 1	4 9	5 4	5 2	5 0	4 9	5 3	5 1	5 0	4 8	5 2	5 1	4 9	4 8	4 7		
等価発光面積			c m ²	2 . 0	5 7	5 5	5 3	5 2	5 6	5 4	5 3	5 2	5 5	5 3	5 2	5 1	5 4	5 3	5 1	5 1	5 0	
2 . 5	5 8			5 6	5 5	5 4	5 7	5 6	5 4	5 3	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 2	5 1			
取付 高さ	器具間隔最大限		3 . 0	5 8	5 7	5 6	5 5	5 8	5 6	5 5	5 4	5 7	5 5	5 5	5 4	5 5	5 5	5 4	5 3	5 2		
	横方向 (A)	縦方向 (B)	4 . 0	5 9	5 8	5 7	5 6	5 9	5 8	5 7	5 6	5 7	5 7	5 6	5 5	5 6	5 6	5 5	5 4	5 3		
H m	1 . 2 8 H m	1 . 2 8 H m	5 . 0	6 0	5 9	5 8	5 7	5 9	5 8	5 8	5 7	5 8	5 7	5 7	5 6	5 7	5 6	5 6	5 5	5 4		
			7 . 0	6 0	6 0	5 9	5 8	6 0	5 9	5 8	5 8	5 8	5 8	5 7	5 7	5 7	5 7	5 6	5 6	5 5		
			1 0 . 0	6 1	6 0	6 0	5 9	6 0	6 0	5 9	5 9	5 9	5 8	5 8	5 8	5 8	5 7	5 7	5 7	5 5		

