

屋内照明器具特性	
品番 (品名)	S L R 9 0 1 5
光源	L L D 2 4 1 0 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 5 2 (0) D B 1
B Z 分類	B Z 1

器具効率			9 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束			0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束			9 1 %																					
保守率			良 中 否	0 . 6 3	0 . 6	7 1	6 4	6 0	5 7	7 0	6 3	5 9	5 7	6 8	6 3	5 9	5 6	6 7	6 2	5 9	5 6	5 5		
				0 . 6	0 . 8	7 7	7 2	6 7	6 5	7 7	7 1	6 7	6 4	7 5	7 0	6 7	6 4	7 4	6 9	6 6	6 4	6 3		
				0 . 5 6	1 . 0	8 2	7 6	7 3	7 0	8 1	7 6	7 2	7 0	7 9	7 5	7 2	6 9	7 7	7 4	7 1	6 9	6 8		
				1 . 2 5	8 5	8 0	7 7	7 4	8 4	8 0	7 7	7 4	8 2	7 9	7 6	7 4	8 1	7 8	7 5	7 3	7 2			
下方投影面積			c m ²	1 . 5	8 7	8 3	8 0	7 8	8 6	8 3	8 0	7 7	8 4	8 1	7 9	7 7	8 3	8 0	7 8	7 6	7 5			
				2 . 0	9 0	8 7	8 4	8 2	8 9	8 6	8 4	8 1	8 7	8 5	8 3	8 1	8 5	8 3	8 2	8 0	7 8			
等価発光面積			c m ²	2 . 5	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 4	8 9	8 7	8 5	8 3	8 7	8 5	8 4	8 2	8 1			
				3 . 0	9 3	9 0	8 8	8 7	9 2	9 0	8 8	8 6	9 0	8 8	8 6	8 5	8 8	8 7	8 5	8 4	8 2			
H m		0 . 7 5 H m	0 . 7 5 H m	4 . 0	9 4	9 2	9 1	8 9	9 3	9 1	9 0	8 9	9 1	9 0	8 9	8 7	8 9	8 8	8 7	8 6	8 4			
				5 . 0	9 5	9 3	9 2	9 1	9 4	9 3	9 1	9 0	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 8	8 5			
				7 . 0	9 6	9 5	9 4	9 3	9 5	9 4	9 3	9 2	9 3	9 2	9 1	9 1	9 1	9 0	9 0	8 9	8 7			
				1 0 . 0	9 7	9 6	9 5	9 4	9 5	9 5	9 4	9 4	9 3	9 3	9 2	9 2	9 2	9 1	9 1	9 0	8 8			

