

屋内照明器具特性	
品番 (品名)	XSZR1011L
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0192057 (0) DB1
BZ分類	BZ1/4.5/BZ2/6.0/BZ1

器具効率		6 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	4 5	4 0	3 6	3 4	4 5	4 0	3 6	3 4	4 4	3 9	3 6	3 4	4 3	3 9	3 6	3 4	3 3
			0 . 6	0 . 8	5 1	4 6	4 3	4 0	5 1	4 6	4 3	4 0	4 9	4 5	4 2	4 0	4 8	4 5	4 2	4 0	3 9
			0 . 5 6	1 . 0	5 5	5 0	4 7	4 5	5 4	5 0	4 7	4 5	5 3	4 9	4 6	4 4	5 1	4 8	4 6	4 4	4 3
				1 . 2 5	5 8	5 4	5 1	4 9	5 7	5 3	5 1	4 8	5 5	5 2	5 0	4 8	5 4	5 2	4 9	4 8	4 7
下方投影面積		c m ²		1 . 5	5 9	5 6	5 3	5 1	5 9	5 5	5 3	5 1	5 7	5 5	5 2	5 1	5 6	5 4	5 2	5 0	4 9
			等価発光面積	c m ²	2 . 0	6 2	5 9	5 7	5 5	6 1	5 8	5 6	5 5	6 0	5 7	5 6	5 4	5 8	5 6	5 5	5 4
取付高さ	器具間隔最大限			2 . 5	6 3	6 1	5 9	5 7	6 2	6 0	5 8	5 7	6 1	5 9	5 8	5 6	6 0	5 8	5 7	5 6	5 4
	横方向 (A) 縦方向 (B)			3 . 0	6 4	6 2	6 0	5 9	6 3	6 2	6 0	5 9	6 2	6 0	5 9	5 8	6 1	5 9	5 8	5 7	5 6
H m	1 . 0 7 H m	1 . 0 7 H m		4 . 0	6 5	6 4	6 2	6 1	6 5	6 3	6 2	6 1	6 3	6 2	6 1	6 0	6 2	6 1	6 0	5 9	5 8
				5 . 0	6 6	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 2	6 2	6 1	6 0	5 9
				7 . 0	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 4	6 5	6 4	6 3	6 3	6 3	6 3	6 2	6 2	6 0
				1 0 . 0	6 7	6 7	6 6	6 6	6 7	6 6	6 5	6 5	6 5	6 5	6 4	6 4	6 4	6 3	6 3	6 3	6 1

