

屋内照明器具特性	
品番 (品名)	XS Z B 8 3 3 1 3
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0193246 (0) DB 1
B Z 分類	BZ3 / 1.8 / BZ4 / 6.0 / BZ5

器具効率		82 % 上方光束 16 % 下方光束 66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否 0.63 0.6 0.56	0.6	50	41	36	32	48	40	35	31	45	38	34	30	42	36	32	29	27	
			0.8	57	48	43	39	55	47	42	38	51	45	40	37	47	42	38	36	33	
			1.0	61	54	48	44	59	52	47	43	55	49	45	42	51	46	43	40	37	
			1.25	65	58	53	49	63	57	52	48	58	53	49	46	54	50	47	44	40	
下方投影面積		cm ²	1.5	68	62	57	53	66	60	55	52	61	56	53	49	57	53	50	47	43	
等価発光面積			2.0	72	66	62	59	69	64	60	57	64	60	57	54	60	57	54	52	47	
取付 高さ	器具間隔最大限		2.5	74	70	66	62	72	67	64	61	67	63	60	58	62	59	57	55	50	
	横方向 (A)		縦方向 (B)		3.0	76	72	68	65	73	70	66	64	68	65	63	60	63	61	59	57
H m	1.07 H m	1.07 H m	4.0	78	75	72	69	75	72	70	67	70	68	66	64	65	63	62	60	55	
			5.0	79	77	74	72	77	74	72	70	72	70	68	66	67	65	64	62	56	
			7.0	81	79	77	75	78	76	75	73	73	72	70	69	68	67	66	65	59	
			10.0	82	81	79	78	80	78	77	75	74	73	72	71	69	68	68	67	60	

