

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | L S E B 3 0 0 3 K            |
| 光源       | LED6200_70_3730 ×1 3730.0 lm |
| 管理番号     | K0161788 ( 0 ) D 1           |
| B Z 分類   | B Z 5                        |

| 器具効率     |           | 100 %           | 反射率  | 天井            | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |   |
|----------|-----------|-----------------|------|---------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|---|
|          |           |                 |      | 壁             | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|          |           |                 |      | 床             | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束     |           | 7 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C | M |
| 下方光束     |           | 93 %            |      |               |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |   |
| 保守率      |           | 良<br>中<br>否     | 0.67 | 0.6           | 56   | 44 | 36 | 31  | 54   | 43 | 35 | 30 | 51   | 41 | 35 | 30 | 48   | 40 | 34 | 29 | 27  |   |   |   |
|          |           |                 | 0.63 | 0.8           | 66   | 54 | 46 | 41  | 64   | 53 | 46 | 40 | 60   | 51 | 44 | 40 | 57   | 49 | 43 | 39 | 36  |   |   |   |
|          |           |                 | 0.56 | 1.0           | 72   | 61 | 54 | 48  | 70   | 60 | 53 | 48 | 66   | 58 | 52 | 47 | 63   | 56 | 50 | 46 | 43  |   |   |   |
|          |           |                 |      | 1.25          | 78   | 68 | 61 | 55  | 76   | 67 | 60 | 55 | 72   | 64 | 58 | 54 | 68   | 62 | 57 | 53 | 49  |   |   |   |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 82            | 73   | 67 | 61 | 80  | 72   | 66 | 60 | 76 | 69   | 64 | 59 | 72 | 66   | 62 | 58 | 54 |     |   |   |   |
|          |           |                 | 2.0  | 88            | 81   | 74 | 69 | 86  | 79   | 73 | 69 | 81 | 76   | 71 | 67 | 78 | 73   | 69 | 65 | 62 |     |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 91            | 85   | 80 | 75 | 89  | 83   | 79 | 74 | 85 | 80   | 76 | 72 | 81 | 77   | 74 | 70 | 67 |     |   |   |   |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 94            | 88   | 84 | 80 | 92  | 87   | 82 | 78 | 88 | 83   | 80 | 76 | 84 | 80   | 77 | 74 | 70 |     |   |   |   |
| H m      | 1.24 H m  | 1.24 H m        | 4.0  | 97            | 93   | 89 | 85 | 95  | 91   | 87 | 84 | 91 | 87   | 84 | 82 | 87 | 84   | 82 | 79 | 75 |     |   |   |   |
|          |           |                 | 5.0  | 99            | 95   | 92 | 89 | 97  | 93   | 90 | 88 | 93 | 90   | 87 | 85 | 89 | 87   | 85 | 83 | 78 |     |   |   |   |
|          |           |                 | 7.0  | 101           | 98   | 96 | 94 | 99  | 97   | 94 | 92 | 95 | 93   | 91 | 89 | 91 | 90   | 88 | 87 | 82 |     |   |   |   |
|          |           |                 | 10.0 | 103           | 101  | 99 | 97 | 101 | 99   | 97 | 96 | 97 | 95   | 94 | 93 | 93 | 92   | 91 | 90 | 85 |     |   |   |   |

