

# 屋内照明器具特性

品番 (品名)	NNQ35941				
光源	LED3000_85_3260 x1 3260.0 lm				
管理番号	K0172559(0)DR1				
BZ分類	BZ6				

器具効率	83%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.81	0.6	43	32	26	21	41	31	25	21	38	29	24	20	35	28	23	19	17	
	中	0.77	0.8	51	40	33	28	49	39	33	28	45	37	31	27	41	34	30	26	23	
	否	0.68	1.0	56	46	39	34	54	45	38	33	49	42	36	32	46	39	34	31	27	
			1.25	61	52	45	40	58	50	44	39	54	47	42	37	50	44	39	36	32	
下方投影面積			1.5	64	56	49	44	62	54	48	43	57	51	45	41	53	47	43	39	35	
			2.0	69	62	56	51	66	60	54	50	61	56	51	47	57	52	49	45	41	
取付高さ	器具間隔最大限		2.5	72	65	60	56	69	63	59	54	64	60	55	52	60	56	52	49	45	
	横方向 (A)	縦方向 (B)	3.0	74	68	64	59	71	66	62	58	66	62	59	55	62	58	55	53	48	
1.5m	2.08m	2.13m	4.0	77	72	68	64	74	70	66	63	69	66	63	60	65	62	59	57	52	
2	2.75	2.69	5.0	79	75	71	68	76	72	69	66	71	68	66	63	67	64	62	60	55	
2.5	3.42	3.28	7.0	81	78	75	72	78	75	73	70	73	71	69	67	69	67	65	64	58	
3	4.08	3.88	10.0	82	80	78	76	80	78	76	74	75	74	72	70	71	69	68	67	61	

