

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | X F X 2 0 0 A E N           |
| 光源       | LED5000_85_830 ×1 830.0 l m |
| 管理番号     | K0192144 ( 0 ) D 1          |
| B Z 分類   | B Z 5                       |

| 器具効率     |         | 100 %           | 反射率     | 天井            | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |       |  |
|----------|---------|-----------------|---------|---------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|-------|--|
|          |         |                 |         | 壁             | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |       |  |
|          |         |                 |         | 床             | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |       |  |
| 上方光束     |         | 4 %             | 室指数     | 照明率 ( X0.01 ) |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z C M |  |
| 下方光束     |         | 96 %            |         |               |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |  |       |  |
| 保守率      |         | 良<br>中<br>否     | 0.83    | 0.6           | 56   | 43 | 35 | 30  | 54   | 42 | 35 | 30 | 51   | 41 | 34 | 29 | 49   | 40 | 34 | 29 | 27  |  |       |  |
|          |         |                 | 0.81    | 0.8           | 65   | 54 | 46 | 40  | 64   | 53 | 45 | 39 | 60   | 51 | 44 | 39 | 57   | 49 | 43 | 38 | 36  |  |       |  |
|          |         |                 | 0.77    | 1.0           | 72   | 61 | 53 | 47  | 70   | 60 | 52 | 47 | 66   | 58 | 51 | 46 | 63   | 56 | 50 | 45 | 42  |  |       |  |
|          |         |                 |         | 1.25          | 78   | 68 | 60 | 54  | 76   | 66 | 59 | 54 | 72   | 64 | 58 | 53 | 69   | 62 | 56 | 52 | 49  |  |       |  |
| 下方投影面積   |         | cm <sup>2</sup> | 1.5     | 82            | 72   | 65 | 60 | 80  | 71   | 64 | 59 | 76 | 69   | 63 | 58 | 72 | 66   | 61 | 57 | 54 |     |  |       |  |
| 等価発光面積   |         | cm <sup>2</sup> | 2.0     | 87            | 79   | 73 | 68 | 85  | 78   | 72 | 67 | 81 | 75   | 70 | 66 | 78 | 73   | 68 | 65 | 61 |     |  |       |  |
| 取付<br>高さ | 器具間隔最大限 |                 | 2.5     | 91            | 84   | 78 | 73 | 89  | 83   | 77 | 73 | 85 | 80   | 75 | 71 | 81 | 77   | 73 | 70 | 66 |     |  |       |  |
|          | 横方向 (A) |                 | 縦方向 (B) | 3.0           | 93   | 87 | 82 | 78  | 91   | 86 | 81 | 77 | 87   | 83 | 79 | 75 | 84   | 80 | 77 | 74 | 70  |  |       |  |
| 1.5m     | 1.92 m  | 1.89 m          | 4.0     | 96            | 92   | 87 | 84 | 95  | 90   | 86 | 83 | 91 | 87   | 84 | 81 | 87 | 84   | 81 | 79 | 75 |     |  |       |  |
| 2        | 2.55    | 2.48            | 5.0     | 98            | 94   | 91 | 87 | 97  | 93   | 89 | 86 | 93 | 90   | 87 | 84 | 89 | 87   | 84 | 82 | 78 |     |  |       |  |
| 2.5      | 3.19    | 3.08            | 7.0     | 101           | 98   | 95 | 92 | 99  | 96   | 93 | 91 | 95 | 93   | 91 | 89 | 92 | 90   | 88 | 86 | 83 |     |  |       |  |
| 3        | 3.84    | 3.68            | 10.0    | 103           | 100  | 98 | 96 | 101 | 99   | 97 | 95 | 97 | 96   | 94 | 92 | 94 | 93   | 91 | 90 | 86 |     |  |       |  |

