

屋内照明器具特性	
品番 (品名)	NNF 4 5 6 5 2 J
光源	LED3500_85_8000 ×1 8000.0 lm
管理番号	K0135231 (0) DB 1
B Z 分類	BZ5

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																	
保守率			良 中 否	0.77	0.6	57	45	37	32	56	44	37	31	53	43	36	31	51	42	36	31	29	
				0.72	0.8	67	56	48	42	66	55	47	42	63	53	47	42	60	52	46	41	39	
				0.68	1.0	74	63	55	50	72	62	55	50	69	61	54	49	67	59	53	49	47	
					1.25	80	70	63	57	78	69	62	57	75	67	61	57	72	66	60	56	54	
下方投影面積			cm ²	1.5	84	75	68	63	82	74	68	63	79	72	67	62	76	70	66	61	59		
				2.0	90	82	76	71	88	81	76	71	85	79	74	70	82	77	73	69	67		
等価発光面積			cm ²	2.5	93	87	82	77	91	86	81	77	88	84	79	76	86	82	78	75	72		
				3.0	96	90	85	81	94	89	85	81	91	87	83	80	88	85	81	79	76		
1.5m		2.05 m	2.05 m	4.0	99	94	91	87	97	93	90	86	94	91	88	85	92	89	86	84	81		
2		2.64	2.64	5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	91	89	87	84		
2.5		3.23	3.24	7.0	103	100	98	95	101	99	97	94	99	97	95	93	96	94	93	91	88		
3		3.85	3.85	10.0	104	102	101	99	103	101	100	98	100	99	97	96	98	97	95	94	91		

