

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40001CQ1 ×2 845.0 lm
管理番号	K0194446 (1) D 1
BZ分類	BZ1

器具効率		15 % 上方光束 8 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.63	0.6	9	8	7	6	8	7	7	6	7	7	6	6	7	6	6	5	5
			0.6	0.8	10	9	8	7	9	8	8	7	8	7	7	7	7	7	6	6	5
			0.56	1.0	11	10	9	8	10	9	8	8	9	8	8	7	8	7	7	7	6
				1.25	11	10	10	9	10	10	9	9	9	9	8	8	8	8	7	7	6
下方投影面積		cm ²		1.5	12	11	10	10	11	10	10	9	9	9	9	8	8	8	8	7	6
				2.0	12	11	11	10	11	11	10	10	10	9	9	9	9	8	8	8	8
取付 高さ	器具間隔最大限			2.5	13	12	11	11	12	11	11	10	10	10	9	9	9	8	8	8	6
	横方向 (A)		縦方向 (B)	3.0	13	12	12	11	12	11	11	11	10	10	10	9	9	9	8	8	6
H m	0.74 H m		0.74 H m	4.0	13	13	12	12	12	12	11	11	10	10	10	9	9	9	9	7	
				5.0	13	13	13	12	12	12	12	11	10	10	10	9	9	9	9	7	
				7.0	13	13	13	13	13	12	12	12	11	11	11	10	9	9	9	7	
				10.0	14	13	13	13	13	13	12	12	11	11	11	11	9	9	9	7	

