

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD5000LCC1 ×2 1140.0 lm
管理番号	K0194456 (1) D 1
BZ分類	BZ1

器具効率		48 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z CM																				
保守率		良 中 否	0.63	0.6	30	26	23	21	28	25	22	21	25	22	21	19	22	20	19	18	16				
			0.6	0.8	33	30	27	25	31	28	26	24	27	25	23	22	24	22	21	20	17				
			0.56	1.0	36	32	30	28	33	30	28	27	29	27	26	24	25	24	23	22	19				
			1.25	38	34	32	30	35	33	31	29	31	29	27	26	26	25	24	24	19					
下方投影面積		cm ²	1.5	39	36	34	32	36	34	32	31	32	30	29	28	27	26	25	25	20					
等価発光面積			2.0	41	38	37	35	38	36	34	33	33	32	30	29	28	27	27	26	21					
取付高さ	器具間隔最大限			2.5	42	40	38	37	39	37	36	35	34	33	32	31	29	28	27	27	21				
	横方向 (A)		縦方向 (B)	3.0	43	41	39	38	40	38	37	36	34	33	32	32	29	29	28	27	21				
H m	1.06 H m		1.09 H m	4.0	43	42	41	40	41	39	38	37	35	34	33	33	30	29	29	28	22				
				5.0	44	43	42	41	41	40	39	39	35	35	34	34	30	30	29	29	22				
				7.0	45	44	43	42	42	41	40	40	36	35	35	35	30	30	30	30	22				
				10.0	45	45	44	44	42	42	41	41	36	36	36	35	31	30	30	30	22				

